

Conveyor Products

PT Max™ Belt Trainer

The PT Max™ is a high performance belt trainer. The patented “pivot & tilt” design delivers superior training action that makes it easy to keep even the most troublesome belts on track permanently. When a belt mistracks as little as 1/2" (13mm), the PT Max begins a pivoting action. This immediately triggers a tilting action that increases the tension in the belt on the side wandering off, and this uneven tension causes the belt to move back to center. Top side and return side models are available. Other features include:



“Pivot & Tilt”

- **Two Sensor Rollers on Each Side** – the increased belt edge surface contact reduces severe edge pressure and eliminates belt edge damage.
- **Pivot Points Will Not Freeze Up** – eliminates a common problem with conventional trainers. A unique universal bearing requires no lubrication and is guaranteed to last.



PT Max
Top Side



PT Max
Return Side

No Risk Performance Guarantee

Our PT Max™ Belt Trainer Center Bearing is guaranteed for 5 years of satisfactory service.

V-Plow

The V-Plow is a “belt cleaner” for the inside of the belt. It keeps rocks, lumps, fines and other debris from getting into the tail pulley and causing damage to the belt, splice, lagging or pulley.



- **Exclusive Blade Design** – the blade’s 20° leading edge spirals debris off the belt.
- **Self-Adjusting Blade** – the plow is installed so the blade floats on the belt and self-adjusts as it wears.
- **Unique Adjuster** – a turnbuckle-type adjuster allows the blade to be fine-tuned to the belt at installation. This means the nose of the plow is accurately positioned so it will not dig into the belt and cause damage to the belt or the plow.
- **UHMW Blade** – for long blade life and less wear and tear on the belt. Replacement blades are economical and easy to change out.
- **Easy to Install** – comes fully assembled and can be placed right into position on the conveyor. Simple step-by-step instructions are included for quick installation.
- **Versatile** – fits any conveyor structure. An optional Clamp Plate Kit is available for mounting on small channel, rope or tube structures. Can be used at the tail pulley or anywhere on the beltline where carryback is a problem.



Flex-Lok™ Skirt Clamps

Eliminating loading point spillage can be done effectively and permanently with Flex-Lok™ Skirt Clamps. These versatile skirt clamps feature an interlocking design that can be installed and readjusted by a single person. When properly installed, the skirt rubber will not rub on the belt or cause premature wear or gouge marks on the belt. Other features include:



- **Unique Wedge Pin** – skirt rubber is inserted and adjusted by simply using a non-metal hammer to unlock the self-contained wedge in the clamp pin and relocking it.
- **Anti-Vibration Clamp Pin** – the wedge in the clamp pin has one side serrated, so when the wedge is pounded into the closed position the teeth lock it in place and guard against loosening due to vibration.
- **Low Maintenance** – all parts interlock for assembly. No nuts and bolts to rust and break off.
- **Safe to Service** – all maintenance can be done safely from the sides of the conveyor.
- **Versatile** – can be used with a range of skirt rubber thicknesses from 5/16" to 1" (8 to 25mm).



Mini Flex-Lok Skirt Clamps

Mini Flex-Lok has been reduced in height to accommodate tight chute configurations and portable equipment with restricted space. Height of the mini clamp plate is 4-1/2" (113mm); the standard clamp plate is 7" (175mm). Mini Flex-Lok will handle a skirt rubber thickness range from 5/16" to 5/8" (8 to 16mm).



Standard Mini

Beltline Maintenance Tools

Flex-Lifter™

Moving a tensioned conveyor belt out of the way to do maintenance work is a tough job. And it can be dangerous if the right tools are not used. The Flex-Lifter is designed to lift tensioned belts easily and safely. It is portable and easy to place on the conveyor. The Flex-Lifter can lift top side (both troughed and flat belts) and return side belts. Each model covers a range of belt widths.



Other Flexco Maintenance Tools

Flexco® 840 Belt Cutter

Makes straight belt end cuts quickly and easily. Adjustable clamp bars hold the belt securely and a double-edged blade cuts cleanly in either direction.



FSK™ Belt Skiver

It simplifies the process of recessing fasteners by accurately and uniformly skiving the belt’s top cover. Increases belt fastener/cleaner compatibility.



Far-Pul® HD® Belt Clamps

Easy-to-use, adjustable belt clamps. Engineered for heavy-duty applications and adjustable to a variety of belt widths.



GOODYEAR
RUBBER PRODUCTS INC.

Call Toll Free: **1-866-711-4673**
WebSales@GoodyearRubberProducts.com

**We Ship
World Wide**