



Flowmaster Attack Lightweight Attack Hose

Flexline Flowmaster Attack											
Size inch mm	Service		Pressure Proof		Burst		Bowl Size		Weight*		Coil Diameter
	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m) lbs. kg	50' (15m) inch mm	
1 25	300	2100	600	4200	900	6300	1-1/4	32	8	3.6	15 381
1-1/2 38	300	2100	600	4200	900	6300	1-13/16	46	16	7.3	16 406
1-3/4 45	300	2100	600	4200	900	6300	2-1/16	52	18	8.2	16 406
2 50	300	2100	600	4200	900	6300	2-5/16	59	20	9.1	17 432
2-1/2 65	300	2100	600	4200	900	6300	2-7/8	73	27	12.2	18 457

Flexline Flowmaster Attack is a lightweight nitrile rubber through-the-weave construction fire hose. Its synthetic jacket is completely protected and locked in by a rubber cover and lining for extra toughness and durability. A heavy rib construction makes this hose resistant to cuts, punctures, impact and abrasion. Flowmaster Attack is a 600 psi (4200 kPa) fire hose that withstands temperatures from 1200°F to -37°F, (649°C to -38°C). Its light-weight design is virtually non-kinking and ideal for municipal fire protection. The standard colors for Flowmaster Attack are yellow and red, 1" size is available in yellow only.

Flowmaster Supply Large Diameter Supply Hose

Flexline Flowmaster Supply											
Size inch mm	Service		Pressure Proof		Burst		Bowl Size		Weight*		Coil Diameter
	psi	kPa	psi	kPa	psi	kPa	inch	mm	100' (30m) lbs. kg	100' (30m) inch mm	
3 75	300	2100	600	4200	900	6300	3-13/32	87	70	31.5	25 635
4 100	225	1575	450	3150	675	4725	4-5/16	110	90	40.5	24 610
5 125	200	1400	400	2800	600	4200	5-3/8	137	109	49.1	27 686

Flexline Flowmaster Supply is a tough large diameter hose with the ability to deliver more water at a lower cost. But it doesn't stop there. It is lightweight, compact and durable with a high resistance to oils, chemicals, ozone and heat. Its tough, high tensile cover and lining, permanently interlocked with the synthetic reinforcement, provide greater abrasion resistance while being snag-proof, kink resistant, and immune to mildew or rot. U.L. labeling is available on 4" (100 mm) and 5" (125 mm) only. The standard colors for Flowmaster Supply are yellow or red.

Flexline FLEX6 Rubber Covered Through-The-Weave Forestry Hose

Flexline FLEX6											
Size inch mm	Service		Pressure Proof		Burst		Bowl Size		Weight*		Coil Diameter
	psi	kPa	psi	kPa	psi	kPa	inch	mm	100' (30m) lbs. kg	100' (30m) inch mm	
1 25	300	2100	600	4200	900	6300	1-1/4	31.8	10	4.5	16 406
1-1/2 38	300	2100	600	4200	900	6300	1-11/16	42.9	17	7.5	18 457

Nitrile rubber covered forestry hoses that require no washing or drying and are mildew resistant. A protective rubber covering resists burns and prevents damage of the textile reinforcement which may be caused by abrasion or hot embers. The standard color is high visibility yellow. There is a minimum order quantity for 1-1/2" size.

Flexline FTP6 Polyester Single Jacket Plastic Lined Forestry Hose

Flexline FTP6											
Size inch mm	Service		Pressure Proof		Burst		Bowl Size		Weight*		Coil Diameter
	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m) lbs. kg	50' (15m) inch mm	
1 25	300	2100	600	4200	900	6300	1-1/4	31.8	7.5	3.4	14 356
1-1/2 38	300	2100	600	4200	900	6300	1-3/4	45	13.5	6.1	16 406

A lightweight polyester jacket, polyurethane lined forestry fire hose that meets the USDA-US Forest Service Specification 5100-187. The standard color for Flexline FTP6 is white. Other colors available are yellow.

* Weight is uncoupled
Non standard diameters available by special arrangement