



SPIRALITE® 960

URETHANE BLENDED DUCT HOSE

- **APPEARANCE/CONSTRUCTION:**

PVC/Polyurethane blended tube with PVC helix.
Corrugated exterior with smooth interior.

- **BENEFITS:**

- Polyurethane blended wall for added abrasion resistance.
- Improved wall design enhances flexibility.
- PVC reinforcement resist crushing.
- Extremely flexible.

- **GENERAL APPLICATIONS:**

- Tight bend areas with light abrasive material transfer.
- Blown insulation applications.
- Ice slinger hose.

- **TEMPERATURE RANGE:**

-10°F to +130°F

- **STANDARD LENGTHS:**

3" thru 6" 100ft.

| NOMINAL SIZE | inch | 3" | 4" | 5" | 6" |
|----------------------------------|---------|------|------|------|------|
| APPROX. O.D. | inch | 3.50 | 4.57 | 5.57 | 6.60 |
| RECOMMENDED W.P. AT 68°F | psi | 10 | 10 | 10 | 7 |
| RECOM. MIN. BEND RADIUS AT 68°F* | inch | 4 | 6 | 6 | 7 |
| APPROX. B.P. AT 68°F | psi | 35 | 35 | 30 | 25 |
| APPROX. WT. | lbs./ft | .86 | 1.09 | 1.38 | 1.69 |

* BEND RADIUS FOR CONTINUOUS SERVICE.