



Farm Pump/Gravity Tank Hose

Series 7173 – No Static Wire, NOT U.L. Listed

For dispensing oil, leaded and unleaded gasoline and diesel fuel from hand pump and gravity feed farm pumps, skid tanks, drums and storage tanks.

4:1 Design factor

>> Lightweight and flexible

Tube	Black Nitrile
Cover	Red Neoprene – Smooth Cover
Reinforcement	Multiple textile spirals
Temperature Range	-40°F to +180°F (-40°C to +82°C)
Branding	PARKER SERIES 7173 FARM PUMP/GRAVITY TANK FUEL HOSE 3/4 in. ID–50 PSI MAX WP, MADE IN USA B2 (month/year)
Brand Description	White Ink
Compare to	Goodyear Aggie Gas; Thermoid Premier Farm Tank

LENGTHS: Random length reels (-50 ft. /+0 ft.) 80% 1 piece, 20% 2 piece. 50 ft. min. length. 1 in. = 300 ft. reels – ¾ in. = 400 ft. reels.

COUPLINGS: Externally crimped NPT couplings – no individual coupling sales, which are sold or quoted separately. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Spirals	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7173-75052	¾	19.1	2	1.063	26.9	29	5.0	50
7173-100052	1	25.4	2	1.375	34.9	46	8.0	50

7173

Applications

- Hand Pumps
- Farm Pumps
- Gravity Tanks



WARNING! Not for service station use! The proliferation of self-service gas stations has created a situation where millions of consumers are daily operators of gasoline pumps. Proper hose selection must take into consideration the amount of use and abuse a hose must withstand during its service life. Only the highest quality, thoroughly tested, UL 330 listed hose must be selected for service station applications. The proper hose plus constant inspection is the best protection against user accidents.

DO NOT USE PARKER FARM PUMP/GRAVITY TANK HOSE FOR FUELING OF AIRCRAFT!