



STEAM-LANCE® 150 Steam Cleaner Hose Series 7250

The hose is designed for tough, constant use in steam cleaning operations in oily environments, and for saturated steam applications. Pressures to 150 PSI and temperatures to 368°F. Validated permanent crimp specs are available.

10:1 Design factor for steam applications

>> Designed to decrease downtime

Tube	Black Nitrile
Cover	Perforated Red Neoprene
Reinforcement	One wire braid
Temperature Range	-20°F to +368°F (-29°C to 187°C)
Branding	PARKER USA 7250 STEAM LANCE® (DATE CODE) 150 PSI MAX WP - B2
Brand Description	Embossed Brand
Compare to	Boston Concord 250 O.R.

LENGTHS: Random lengths on nominal 500 ft. reels. Max. 600 ft., min. 400 ft., 5 pieces max. with 50 ft. min. length.

COUPLINGS: **WARNING! Use ONLY Parker recommended hose/coupling combinations for Steam Applications!**

For permanent crimp specifications, refer to CrimpSource. Coupling options include: Series 7610, 7613, 7615, 7692. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Braids	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7250-381	3/8	9.5	1	0.781	19.8	28	5.0	150
7250-501	1/2	12.7	1	0.906	23.0	34	7.0	150
7250-751	3/4	19.1	1	1.187	30.1	51	9.5	150
7250-1001	1	25.4	1	1.500	38.1	75	12.0	150

7250

Applications

- Food Processing
- Plant Steam Service
- Refineries



WARNING! Water changes to hot water and phases of steam when subjected to heat and pressure. The greater the pressure, the higher the temperature required to achieve, maintain a steam phase. If the steam escapes, dangerous quantities of heat are released very suddenly. Hot water, low pressure steam, and high pressure steam can cause severe scalding or fatal burns.

USE ONLY STEAM HOSES DESIGNED FOR STEAM APPLICATIONS.



WARNING! Failure to properly use, maintain, test and inspect steam hose assemblies can result in injury to personnel or damage to property.