

PROCO™

STYLE 710

ProFlex flanged rubber check valves



Table 2: Sizes • Drilling • Weights

NOMINAL ¹ PIPE SIZE Inch / (mm)	Standard Dimensions for PROCO Style 710			Standard Drilling for PROCO Style 710				WEIGHT ² lbs / (kgs)
	Length Inch / (mm)	Duckbill Height Inch / (mm)	Flange O.D. Inch / (mm)	Bolt Circle Inch / (mm)	No. of Holes	Size of Holes Inch / (mm)		
1	(25)	4 (102)	2.125 (54)	4.25 (107.95)	3.13 (79.50)	4	0.625 (15.9)	3 (1.4)
1.5	(40)	5 (127)	2.625 (67)	5.00 (127.00)	3.88 (98.55)	4	0.625 (15.9)	4 (1.8)
2	(50)	6.5 (165)	3.875 (99)	6.00 (152.40)	4.75 (120.65)	4	0.750 (19.1)	6 (2.7)
2.5	(65)	7.5 (191)	4.625 (118)	7.00 (177.80)	5.50 (139.70)	4	0.750 (19.1)	8 (3.6)
3	(80)	8.5 (216)	5.500 (140)	7.50 (190.50)	6.00 (152.40)	4	0.750 (19.1)	10 (4.5)
4	(100)	10 (254)	7.375 (188)	9.00 (228.60)	7.50 (190.50)	8	0.750 (19.1)	14 (6.4)
5	(125)	12 (305)	8.750 (223)	10.00 (254.00)	8.50 (215.90)	8	0.875 (22.2)	17 (7.7)
6	(150)	13 (330)	10.500 (267)	11.00 (279.40)	9.50 (241.30)	8	0.875 (22.2)	22 (10.0)
8	(200)	15 (381)	13.750 (350)	13.50 (342.90)	11.75 (298.45)	8	0.875 (22.2)	27 (12.2)
10	(250)	17 (423)	17.000 (432)	16.00 (406.40)	14.25 (361.95)	12	1.000 (25.4)	39 (17.7)
12	(300)	19 (483)	19.625 (499)	19.00 (482.60)	17.00 (431.80)	12	1.000 (25.4)	62 (28.1)
14	(350)	21 (533)	24.750 (629)	21.00 (533.40)	18.75 (476.25)	12	1.250 (31.8)	81 (36.7)
16	(400)	24 (610)	26.500 (674)	23.50 (596.90)	21.25 (539.75)	16	1.250 (31.8)	125 (56.7)
18	(450)	26 (661)	29.750 (756)	25.00 (635.00)	22.75 (577.85)	16	1.250 (31.8)	210 (95.3)
20	(500)	32 (813)	31.500 (801)	27.50 (698.50)	25.00 (635.00)	20	1.250 (31.8)	312 (141.5)
24	(600)	42 (1067)	43.000 (1093)	32.00 (812.80)	29.50 (749.30)	20	1.375 (34.9)	410 (186.0)
28	(700)	45 (1143)	46.000 (1169)	36.50 (927.10)	34.00 (863.60)	28	1.375 (34.9)	483 (219.1)
30	(750)	47 (1194)	49.000 (1245)	38.75 (984.25)	36.00 (914.40)	28	1.375 (34.9)	555 (251.7)
32	(800)	53 (1346)	51.000 (1296)	41.75 (1060.45)	38.50 (977.90)	28	1.625 (41.3)	605 (274.4)
36	(900)	58 (1473)	55.250 (1404)	46.00 (1168.40)	42.75 (1085.85)	32	1.625 (41.3)	665 (301.6)
42	(1050)	62 (1575)	66.250 (1683)	53.00 (1346.20)	49.50 (1257.30)	36	1.625 (41.3)	965 (437.7)
48	(1200)	72 (1829)	74.500 (1893)	59.50 (1511.30)	56.00 (1422.40)	44	1.625 (41.3)	1005 (455.9)
54	(1350)	74 (1880)	78.250 (1988)	66.25 (1682.75)	62.75 (1593.85)	44	2.000 (50.8)	1085 (492.1)
60	(1500)	82 (2083)	85.000 (2159)	73.00 (1854.20)	69.25 (1758.95)	52	2.000 (50.8)	1285 (582.9)
72	(1800)	98 (2489)	105.000 (2667)	86.50 (2197.10)	82.50 (2095.50)	60	2.000 (50.8)	1500 (680.4)

Notes: 1. Larger sizes available upon request.
2. Weights are approximate.

