Dura Pak - Type DP

Nylon Double Jacket Attack Hose


When introduced, Dura-Pak started an industry-wide trend toward lightweight hi-rise hose. Originally designed for back-pack use, Dura-Pak folds tightly for small spaces, hose beds and hi-rise packs. Because it is so durable many departments have selected Dura-Pak for frontline attack duties.

Properties and Construction

- Dura-Pak is a double jacket municipal fire hose with both jackets made from 100% high strength, low stretch, air-entangled nylon along with a lining of thermoplastic polyurethane for reduced weight while remaining kink resistant.
- Reverse twill weave of the inner jacket provides a smooth waterway, comparable only to Ponn Conquest.
- Standard Dura-Cote[™] protective treatment greatly increases abrasion, heat, flame and petrochemical resistance while virtually eliminating water pick-up. When treated, Dura-Pak is protected from mildew and no drying is required.
- Lining remains flexible to temperatures as low as -40°F (-40°C) and is highly resistant to ozone and oxidation.
- Suitable for C.A.F.S. and foam concentrate applications.
- Polyurethane lining material meets National Sanitation Foundation (NSF) Standard 61 for drinking water.
- National Fire Hose Dura-Pak is manufactured in accordance with NFPA 1961 standard, latest edition within our ISO-9001: 2000 certified quality assurance system.

| - | | | | | | | |
|--------|-----------------|---------------|-------------|-----------------------------|---------------|---------------------------|--------------|
| SIZE | SERVICE TEST | PROOF TEST | BURST | WEIGHT (For 50' Coupled) | FLAT WIDTH | HOSE BED Volume (100') | BOWL SIZE |
| | PSI (kPa) | PSI (kPa) | PSI (kPa) | LBS (KG) | IN | FT ³ | IN |
| 1-1/2" | 400 (2760) | 800 (5515) | 1200 (8275) | 13 (5.9) | 2.80 | 1.0 | 1-15/16 |
| 1-3/4" | 400 (2760) | 800 (5515) | 1200 (8275) | 15 (6.8) | 3.20 | 1.0 | 2-3/16 |
| 2-1/2" | 400 (2760) | 800 (5515) | 1200 (8275) | 23 (10.4) | 4.50 | 1.5 | 3 |
| 3" | 400 (2760) | 800 (5515) | 1200 (8275) | 31 (14.1) | 5.30 | 2.0 | 3-17/32 |

| | How to | Order | | | | | | |
|----|--------|--|------------------------|--|--|-------------------|--------------------|------|
| | DP | 17X50 | | Y | 15 | N | | |
| | TYPE | HOSE X | HOSE LENGTH | COLOR | | THREAD TYPE | COUPLING | |
| | DP | 15 = 1-1/2" 17 = 1-3/4" 25 = 2-1/2" 30 = 3" | 50 = 50' 100 = 100' | $\begin{array}{l} Y = Yellow \\ R = Red \\ B = Blue \\ O = Orange \\ G = Green \\ T = Tan \end{array}$ | 15 = 1-1/2" 20 = 2" 25 = 2-1/2" 30 = 3" | N = NH I = IPT | Blank= Aluminum | |
| GO | | YE | AR | | | | | 4673 |



Construction:

Nylon Double Jacket Polyurethane Inner Liner **Temperature Range:** -40° to 150°F (-40° to 65°C) **Couplings Available:** Aluminum NH/NST or IPT Threaded







POTABLE



FIRE HOSI