





# **Polyester Double Jacket Attack Hose**

Our National Fire Hose 8D is a municipal grade double jacket hose with a lightweight EPDM rubber liner that meets all the requirements of NFPA 1961. It is designed for use as an attack handline hose and is manufactured to a service test pressure of 400 psi (2760 kPa) to handle all fireground challenges with ease.

Should one desire an upgraded design with similar materials using a rubber adhesive, UL or FM certification, or if a woven-in stripe is required for identification purposes, consider our **Ponn Supreme** hose found on pages M-6 and M-7.


# **Properties and Construction**

- Exceptional quality, double jacket, rubber lined municipal fire hose made from 100% high tensile strength polyester yarn with a lining of extruded EPDM.
- Optional Dura-Cote™ treatment greatly increases abrasion, heat, flame and petrochemical resistance while virtually eliminating water pick-up. When treated, 8D is protected from mildew and no drying is required.
- Hose remains flexible to temperatures as low as -40°F (-40°C) and is highly resistant to ozone and oxidation.
- National Fire Hose 8D hose is manufactured in accordance with NFPA 1961 standard, latest edition within our ISO-9001: 2000 certified quality assurance system.

SIZE	SERVICE TEST	PROOF TEST	BURST	WEIGHT (For 50' Coupled)	FLAT WIDTH	HOSE BED Volume (100')	BOWL SIZE
	PSI (kPa)	PSI (kPa)	PSI (kPa)	LBS (KG)	IN	FT <sup>3</sup>	IN
1"	400 (2760)	800 (5515)	1200 (8275)	13 (5.9)	2.10	1.0	1-1/2
1-1/2"	400 (2760)	800 (5515)	1200 (8275)	16 (7.3)	2.80	1.0	1-15/16
1-3/4"	400 (2760)	800 (5515)	1200 (8275)	17 (7.7)	3.20	1.5	2-3/16
2"	400 (2760)	800 (5515)	1200 (8275)	22 (10)	3.70	1.5	2-1/2
2-1/2"	400 (2760)	800 (5515)	1200 (8275)	28 (12.7)	4.50	2.0	3
3"	400 (2760)	800 (5515)	1200 (8275)	39 (17.7)	5.30	3.0	3-17/32

## **How to Order**

8D	17X	50	Y	15	N	
TYPE	HOSE X	HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL
8D	10 = 1" 15 = 1-1/2" 17 = 1-3/4" 20 = 2" 25 = 2-1/2" 30 = 3"	50 = 50' 100 = 100'	Y = Yellow R = Red B = Blue O = Orange G = Green T = Tan W = White (U	10 = 1" 15 = 1-1/2" 20 = 2" 25 = 2-1/2" 30 = 3"	N = NH I = IPT	Blank= Aluminum



#### **Construction:**

Polyester Double Jacket **EPDM Rubber Inner Liner** 

### **Temperature Range:**

-40° to 150°F (-40° to 65°C)

#### **Couplings Available:**

Aluminum NH/NST or IPT Threaded

#### **Hose Colors:**







GOODYEAR Call Toll Free: 1-866-711-4673
WebSales@GoodyearRubberProducts.com