

Booster Hose - Type 2B

Two-Braid Synthetic Rubber Booster Hose

Performance Features:

Snap-tite 2B Booster hose is a high quality all-purpose fire engine booster hose product that can be charged while still on the reel.

Built to take rugged treatment, this hose has a red, synthetic rubber cover that resists abrasion while providing a smooth surface for easy handling. This hose is engineered to be dimensionally stable and will not flatten or crush on reels. This hose is designed to provide a constant working pressure up to 800 psi (5510 kPa) while staying flexible in temperatures as low as -40°F (40°C).

How to Order

2B	07X50		R	10	N	KP
TYPE	HOSE I.D.	x HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL
2B	07 = 3/4" 10 = 1"	50 = 50' 100 = 100' 150 = 150' 200 = 200'	R = Red	10 = 1"	N = NH I = IPT	KP = Chrome Plated Brass Blank = Aluminum

Part Number Example: **2B07X50R10NKP** = 2B Hose, 3/4" ID by 50' Length, Red, 1" NH/NST Threaded Chrome Plated Coupling

Construction:

Red Synthetic Rubber Cover
Two High Strength Textile Braids
Black Synthetic Rubber Liner

Temperature Range:

-40° to 180°F (-40° to 80°C)

Couplings Available:

Chrome Plated Brass or Aluminum
NH/NST or IPT Threaded

Hose Colors:

SIZE	SERVICE TEST	PROOF TEST	BURST	WEIGHT (For 50' Coupled)	BOWL SIZE
	PSI (kPa)	PSI (kPa)	PSI (kPa)	LBS (KG)	IN
3/4"	800 (5515)	1600 (11000)	2400 (16500)	52 (23.6)	1-1/4
1"	800 (5515)	1600 (11000)	2400 (16500)	70 (31.8)	1-19/32

Quik Draw™ - Type 2F

Light Duty Polyester Single Jacket Forestry Hose

Performance Features:

Quik Draw™ is a small diameter, lightweight, compact single jacket fire hose using standard 3/4" brass Garden Hose Thread (GHT) fittings having a working pressure of 150 psi (1030 kPa). This high tenacity filament polyester, polyurethane lined hose can be ordered with or without Snap-tite's Dura-Cote™ treatment that minimizes abrasion and pin-holing. With 50' of Quik-Draw™ weighing only 1.25 lbs and a coil diameter of around 9 inches, this hose can be taken almost anywhere.

How to Order

2F	06X50		W	07	GH	B
TYPE	HOSE I.D.	x HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL
2F	06 = 5/8" 50 = 50'		Y = Yellow W=White (Uncoated)	07 = 3/4"	GH = Garden Hose	B= Brass

Part Number Example: **2F06X50W07GHB** = 2F Quik Draw Forestry Hose, 5/8" ID by 50' Length, White, 3/4" Brass

Construction:

Polyester Single Jacket
Polyurethane Lined Hose

Coating:

Optional Dura-Cote™ (w/color)

Temperature Range:

-40° to 150°F (-40° to 65°C)

Couplings Available:

Brass Garden Hose

Hose Colors:



SIZE	MAX. OPERATING PRESSURE	BURST	WEIGHT (For 50' Coupled)
	PSI (kPa)	PSI (kPa)	LBS (KG)
5/8"	150 (1035)	600 (4140)	1.25 (0.6)