

Hose information is subject to change. For full details, visit our website or contact Customer Service.

FUEL LINE, VAPOR EMISSION & CRANKCASE VENTILATION - SIMILAR TO SAE 30R7

This durable, quality-made hose meets and/or exceeds all SAE J30R7 specifications. It is used for conveying most current types of fuels in automobiles, trucks and buses. This hose is also an aftermarket standard. It provides excellent service for original equipment, wholesalers, aftermarket packagers and auxiliary tank manufacturers. This hose provides superior temperature service and operates in a wide range from -29°F to +257°F. It features an NBR tube and an NBR/PVC cover reinforced with multiple spiral polyester. This combination helps keep the hose flexible while standing up to oil, grease, ozone and under-hood temperatures generated by today's automotive engines. It is available in a variety of sizes and packaging options to suit your application.



- Cover Color:** Black
- Oil Resistance:** Medium-High
- Construction:**
 - Tube:** NBR, RMA Class A
 - Cover:** NBR/PVC, RMA Class B
 - Reinforcement:** Spiral polyester yarn
- Temperature Range:** -29°F to +257°F
-34°C to +125°C
- Packaging:** 25 ft. lengths – 10 lengths per master carton
50 ft. lengths – 5 lengths per master carton
250 ft. reel – maximum 2 lengths per reel
700 ft. reel – maximum 2 lengths per reel

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
25 ft. Coil											
00667503225▲	3/16	4.76	0.41	10.32	2	50	0.34	1.25	31.75	0.07	0.10
00667504225▲	1/4	6.35	0.50	12.70	2	50	0.34	1.50	38.10	0.09	0.13
00667505225▲	5/16	7.94	0.56	14.29	2	50	0.34	2.00	50.80	0.11	0.16
00667506225▲	3/8	9.53	0.63	15.88	2	50	0.34	2.25	57.15	0.12	0.18
50 ft. Coil											
00667503252▲	3/16	4.76	0.41	10.32	2	50	0.34	1.25	31.75	0.07	0.10
00667504252▲	1/4	6.35	0.50	12.70	2	50	0.34	1.50	38.10	0.09	0.13
00667505252▲	5/16	7.94	0.56	14.29	2	50	0.34	2.00	50.80	0.11	0.16
00667506252▲	3/8	9.53	0.63	15.88	2	50	0.34	2.25	57.15	0.12	0.18
250 ft. Reel											
00667503298▲	3/16	4.76	0.41	10.32	2	50	0.34	1.25	31.75	0.07	0.10
00667504298	1/4	6.35	0.50	12.70	2	50	0.34	1.50	38.10	0.09	0.13
00667505298	5/16	7.94	0.56	14.29	2	50	0.34	2.00	50.80	0.11	0.16
00667506298	3/8	9.53	0.63	15.88	2	50	0.34	2.25	57.15	0.12	0.18
700 ft. Reel											
00667503299	3/16	4.76	0.41	10.32	2	50	0.34	1.25	31.75	0.07	0.10
00667504299	1/4	6.35	0.50	12.70	2	50	0.34	1.50	38.10	0.09	0.13
00667505299	5/16	7.94	0.56	14.29	2	50	0.34	2.00	50.80	0.11	0.16
00667506299	3/8	9.53	0.63	15.88	2	50	0.34	2.25	57.15	0.12	0.18

▲ = Make To Order (MTO)