CHIEW/LC/AL

Hose information is subject to change. For full details, visit our website or contact Customer Service.

## **TRANSPORTER<sup>®</sup> ULTRA-CHEM<sup>™</sup>**

Transporter Ultra-Chem hose has been engineered to be extremely flexible. This hose will handle 98% of all common industrial chemicals. Ultra-Chem is ideal for pressure, gravity flow and suction service. This hose has been rated at full vacuum. The green EPDM cover is abrasion and chemical resistant. This hose can also come with a black EPDM cover. For the temperature range of this hose, please see the Chemical Resistance Guide. Note: Working pressures reflect a permanent type coupling such as swage or internally expanded. For banded type couplings, the working pressure should reflect 65% of the ratings listed. A See Chemical Hose Warnings, pages 9 and 128.



Cover Color: Oil Resistance: Construction:	Green High at 70°F, not rated at 140°F
Tube:	UHMWPE backed with compatible rubber layer
Cover:	EPDM
Reinforcement:	Multiple synthetic textile cords and a dual wire helix(es).
Temperature Range:	Maximum temperature limitation +180°F (82°C) for most chemicals
Packaging:	100 ft. maximum

We Ship World Wide

Product Number	<b>Nominal I.D.</b> (inches) (mm)		Nominal O.D. (inches) (mm)		Plies	Working Pressure (psi) (Mpa)		Min. Bend Radius (inches) (mm)		<b>Weight</b> (lb/ft) (Kg/m)	
Green											
17709008002	1	25.40	1.47	36.75	2	250	1.72	4.00	101.60	0.53	0.79
17709009002	1-1/4	31.75	1.78	44.50	2	250	1.72	4.00	101.60	0.75	1.12
17709010002	1-1/2	38.10	2.08	52.00	2	250	1.72	4.00	101.60	0.96	1.43
17709012002	2	50.80	2.58	64.50	2	250	1.72	6.00	152.40	1.30	1.93
17709013002	2-1/2	63.50	3.13	78.25	2	200	1.38	8.00	203.20	1.77	2.63
17709014002	3	76.20	3.66	91.50	2	200	1.38	9.00	228.60	2.09	3.11
17709016002	4	101.60	4.70	117.50	2	150	1.03	12.00	304.80	2.92	4.35
17709018002	6	152.40	6.90	172.50	4	150	1.03	30.00	762.00	5.77	8.59
Black											
17709300002	1	25.40	1.47	36.75	2	250	1.72	4.00	101.60	0.52	0.77

WebSales@GoodyearRubberProducts.com

▲ = Make To Order (MTO)

