SS131 HEAVY DUTY MULTI-PURPOSE DISCHARGE HOSE



- Heavy duty, ultra-high pressure discharge hose designed for multi-purpose use and a variety of tough applications.
- Specially compounded tube is oil and heat resistant.
- All purpose cover is abrasion and ozone resistant.

Tube: Extruded specially compounded Nitrile.


Reinforcement: Textile.

Cover: Abrasion resistant rubber.

Temperature: -40° to +180°F.

I.D.	0.D.	REINFORCEMENT	WORKING Pressure PSI	WEIGHT LB/FT
1 ¹ /2"	23/8"	6 plies	1000	1.53
2"	3"	6 plies	1000	2.01
3"	4 ¹ /8"	6 plies	1000	3.20
4"	5 ³ /16"	6 plies	800	4.51

SS145 HEAVY DUTY OIL AND GAS HOSE



• Cover is oil, abrasion and chemical resistant.

Tube: Extruded Nitrile.

Reinforcement: Textile with internal static wire. **Cover:** Specially compounded Nitrile.

Temperature: -40° to +180°F.

			WORKING	WEIGHT
I.D.	0.D.	REINFORCEMENT	PRESSURE PSI	LB/FT
1 ¹ /2"	23/8"	4 plies	300	1.34
2"	2 ⁷ /8"	4 plies	300	1.69
3"	37/8"	4 plies	300	2.34
4"	4 ⁷ /8"	4 plies	300	3.11
6"	7 ¹ /16"	6 plies	300	5.64

SS160 MUD DISCHARGE HOSE





SS 145 - TITAN OIL & GAS HO

Tube: Extruded specially compounded Nitrile.
Reinforcement: Textile.
Cover: SBR.

Temperature: -40° to +180°F.

I.D.	0.D.	REINFORCEMENT	WORKING Pressure PSI	WEIGHT LB/FT
3"	37/8"	4 plies	300	2.30
4"	4 ⁷ /8"	4 plies	300	3.06
5"	5 ⁷ /8"	4 plies	300	3.75
6"	7 ¹ /16"	6 plies	300	5.54



Call Toll Free: 1-866-711-4673
WebSales@GoodyearRubberProducts.com