

- Heavy Duty Brass
- Full Port For Full Flow
- 600 WOG/150 WSP
- Prevents Electrolysis
- Eliminates Galvanic Corrosion
- Threaded Ends Comply with ANSI b2.1.20.1
- Solder Ends Comply with ANSI B16.18
- Unibody Construction
- Fits Most Circulator Pumps
- Quick Quarter Turn Ball Valve Purge/Drain
- Available for High Velocity Pumps
- Adjustable Stem Packing Nut for Longer Life

- Eliminates Leak Paths
- Saves Space with no Reduction in Performance
- Eliminates Multiple Fittings and Reduced Port Alternatives that Can Alter a System
- High-Flow Hose Drain
- Reversible Handles
- Easy Service
- Shorter Installation Times
- Step Saving Valves that are **GUARANTEED FOR LIFE!**

- Easy Two Step Color Coded Union Connections
- Easy Quarter Turn Ball Valve Operation
- Full Port Throughout Entire Valve Body
- Individually Controlled Drain Outlet
- Easy Cleaning or Flushing of System
- 304 S.S. "T" Handle
- 3/4" Outlet for Pressure Relief Valve
- Heavy Forged Brass
- Conforms to NSF 61-9
- Patent Pending Design
- Allows for One Man Full Diagnostic Testing of Heater Unit

Isolator® is a registered trademark of Webstone Co. INC

Teflon® is a registered trademark of DUPONT
Isolator® EXP™ is a registered trademark of Webstone Co. Inc.

THE ONLY WAY TO ISOLATE CIRCULAR PUMPS

STEP SAVING VALVES FOR THE PROFESSIONAL

THE ONLY WAY TO IN ALL ANY TANKLESS WATER HEATER



ISOLATOR w/ DRAIN
IPS X FLANGE X HOSE
1/2" TO 2"
SWT X FLANGE X HOSE
1/2" TO 2"

ISOLATOR
IPS X FLANGE
1/2" TO 2"
SWT X FLANGE
1/2" TO 2"



PRO-PAL
UNION X SWT w/ HI-FLOW
HOSE DRAIN 3/4" TO 1 1/2"
UNION X IPS w/ HI-FLOW
HOSE DRAIN 3/4" TO 1 1/2"

PRO-PAL
CXC BALL VALVE w/
HI-FLOW HOSE DRAIN 1/2" - 2"
IPS BALL VALVE w/
HI-FLOW HOSE DRAIN 1/2" - 2"

PRO-PAL
PRIMARY LOOP

PRO-PAL
IPS X UNION
3/4" TO 1 1/2"

PRO-PAL
CXC TEE w/



HOT
ISOLATOR EXP
UNION X IPS
UNION X SWT

COLD
ISOLATOR EXP
UNION X IPS
UNION X SWT

