

Hy-T® Black Heater Hose



Application: Designed for heater hose applications where resistance to antifreeze coolants and underhood temperatures are required.

Construction

Tube: Black Versigard (EPDM)

Reinforcement: 2-Spiral Synthetic

Cover: Black Versigard (EPDM)

Temperature Range F & C: -40°F to +257°F(-40°C to +125°C)

SAE Specifications: Similar to SAEJ20R3

Goodyear Engineered Products Specifications: 580001

Length: See table below. 6' (bag), 50' (carton), 250' (reel)

Brand Layline: HY-T® Heater Hose 5/8"(15.9MM) Made in USA Goodyear.

Installation: See selection of Goodyear EP clamps and connectors, and Goodyear EP's E-Z Coil™

Warning: Do not use for fuel or oil transfer applications.

Part Number	ID(in.)	OD(in.)	Length(ft.)	Burst Pressure(PSI)	Weight(lbs./ft.)
64995	5/16	0.63	50	250	0.14
64997	3/8	0.69	50	250	0.16
65070	1/2	0.77	6	250	0.17
65000	1/2	0.77	50	250	0.17
65018	1/2	0.77	250	250	0.17
65071	5/8	0.91	6	250	0.20
65004	5/8	0.91	50	250	0.20
65005	5/8	0.91	250	250	0.20
65072	3/4	1.05	6	200	0.24
65009	3/4	1.05	50	200	0.24
65010	3/4	1.05	250	200	0.24
65012	1	1.34	50	175	0.37



For clamps and connectors see pages 46 - 47.



See Goodyear EP's E-Z Coil™ on page 28.