

Fuel Fill Hose SAE 30R6



Application: Designed for auxillary gas tanks or as a connection between filler neck and tank where a slight hose bend is required.

Construction

Tube: Black Chemigum (Nitrile)

Reinforcement: Textile

Cover: Black Hypalon* (CSM)

Temperature Range F & C: -40°F to +212°F (-40°C to +100°C)

SAE Specifications: SAE J30R6

Product Specification: 538959

Installation: See selection of Goodyear EP clamps

Part Number	ID(in.)	OD(in.)	Leg Lengths(in.)	Angle	Working Pressure(PSI)
59200	1 1/2	1 7/8	8 X 8	45	20
59201	1 3/4	2 1/8	8 X 8	45	20
59202	2	2 3/8	8 X 8	45	20
59203	2 1/4	2 5/8	8 X 8	45	20
59204	2 1/2	2 7/8	8 X 8	45	20
59205	1 1/2	1 7/8	8 X 8	90	20
59206	1 3/4	2 1/8	8 X 8	90	20
59207	2	2 3/8	8 X 8	90	20
59208	2 1/4	2 5/8	8 X 8	90	20
59209	2 1/2	2 7/8	8 X 8	90	20
59210	1 1/2	1 7/8	36	Straight	20
59211	1 3/4	2 1/8	36	Straight	20
59212	2	2 3/8	36	Straight	20
59213	2 1/4	2 5/8	36	Straight	20
59214	2 1/2	2 7/8	36	Straight	20



For clamps see page 47.

*Hypalon is registered by DuPont Dow Elastomers, LLC.