


Hose

High Working Pressure

 Refer to warnings and safety information on pages 3-4 and page 38.

Boston Contractors Air



Tube: Nitrile (RMA Class A)

Reinforcement: Wire, 1 or 2 Braid

Cover: Neoprene/Pinpricked

Color: Yellow

Temperature Range: -40°F To +200°F

Type Of Branding: Ink Print

Working Pressure: 500-1000 PSI

Type Of Coupling: 430 'U' Series, Non-Reattachable (Swaged), Interlocking, or Steel Nipple. Clamps —Interlocking.

Features:

- Neoprene cover
- Nitrile tube (RMA Class A)
- Continuous permanent brand
- Wide range of sizes

Advantages:

- Abrasion, oil, and weather resistant
- Good oil resistance
- Easy identification
- Many applications

Markets:

- Construction Industry
- Oil Field Equipment
- Drilling Equipment
- Mining

Applications:

- Provide power to air-operated construction equipment. (Bull lines, jackhammer, etc.)
- Power air-operated drills, boring, and mining equipment

PRODUCT NUMBER	NOMINAL I.D. (IN.)	NOMINAL I.D. (MM)	BRAID	NOMINAL O.D. (IN.)	NOMINAL O.D. (MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	STANDARD LENGTH (FT)
H962208	1/2	12.7	1	15/16	23.8	34	1,000	50
H962208-100								100
H962208-150								150
H962212	3/4	19.1	1	1-3/16	30.2	44	1,000	50
H962212-100								100
H962212-150								150
H962216	1	25.4	1	1-1/2	38.1	61	850	50
H962216-100								100
H962216-150								150
H962220	1-1/4	31.8	1	1-23/32	43.7	81	500	50
H962220-100								100
H962220-150								150
H962224	1-1/2	38.1	2	2-1/8	53.9	150	500	50
H962224-100								100
H962224-150								150
H962232	2	50.8	2	2-21/32	67.4	204	500	50
H962232-100								100
H962232-150								150