

Hose

Medium Working Pressure

 Refer to warnings and safety information on pages 3-4 and page 38.

Boston Concord Air



Tube: Nitrile

Reinforcement: Fiber, 2 Braid or 2 Ply

Cover: Neoprene 1/2", 3/4" & 1" Pinpricked
Vinyl Nitrile 1-1/4", 1-1/2", 2" & 3" Pinpricked

Color: Red

Temperature Range: -40°F To +200°F

Type Of Branding: Impression

Working Pressure: 300-400 PSI

Type Of Coupling: 'U' Series or 430 'U' Series, Interlocking, Non-Reattachable (Swaged), Quick Acting, Long Shank, Steel Nipple. Clamps —Interlocking or Bands.

Features:

- Neoprene cover
- Nitrile tube
- Continuous permanent brand
- Two textile braids or ply

Advantages:

- Abrasion, oil, and weather resistant
- Good oil resistance
- Easy identification
- Easy to handle
- Kink resistant

Markets:

- Construction Industry
- Forest Industry
- Metal Working
- Mining

Applications:

- Provide power to air-operated construction equipment
- Transfer air and water
- Power air-operated drills, boring, and mining equipment

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	REINF.	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	MTO* MIN. ORDER QTY.	STANDARD LENGTH (FT)
H600208	1/2	12.7	2 Br	29/32	23.0	31	400	—	50
H600208-100									100
H600208-150									150
H600212	3/4	19.1	2 Br	1-3/16	30.2	46	400	—	50
H600212-100									100
H600212-150									150
H600216	1	25.4	2 Br	1-1/2	38.1	67	400	—	50
H600216-100									100
H600216-150									150
H600220	1-1/4	31.8	2 Ply	1-13/16	46.0	86	400	—	50
H600220-100									100
H600220-150									150
H600224	1-1/2	38.1	2 Ply	2-1/16	52.4	99	400	—	50
H600224-100									100
H600224-150									150
H600232	2	50.8	2 Ply	2-5/8	66.7	127	300	—	50
H600232-100									100
H600232-150									150
H600248	3	76.2	2 Ply	3-9/16	90.49	192	200	600	50
H600248-100									100
H600248-150									150

*MTO—Made To Order