

# Hose

## Low Working Pressure

 Refer to warnings and safety information on pages 3-4 and page 38.

### Boston Shock-Safe



**Tube:** Nitrile (non-conductive)  
**Reinforcement:** Fiber, 2 Braid  
**Cover:** Vinyl Nitrile (non-conductive)  
**Color:** Red  
**Temperature Range:** -40°F To +180°F  
**Type Of Branding:** Ink Print  
**Working Pressure:** 275 PSI  
**Type Of Coupling:** 'U' Series, Barbed Inserts, Quick Acting, Long Shank, or Steel Nipple. Clamps—Brass Collar, Interlocking, Single Bolt, Band or Wire.

#### Features:

- Vinyl nitrile cover
- Nitrile tube
- Continuous permanent brand
- Non-conductive
- Each reel factory tested to exceed minimum electrical resistivity of one megaohm per inch at 1000 volts D.C.

#### Advantages:

- Abrasion, oil, and weather resistant
- Medium oil resistance
- Easy identification
- Suitable for use around electrical equipment
- Safety

#### Markets:

- Metal Working
- Utility Company
- Aluminum Industry

#### Applications:

- Use as general purpose air/water hose where hoses must be non-conductive

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	BRAID	NOMINAL O.D. (IN.) (MM)		APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	STANDARD REELS (FT)
H994904-500R	1/4	6.3	2	19/32	15.1	15	275	500
H994906-500R	3/8	9.5	2	23/32	18.3	19	275	500
H994908-500R	1/2	12.7	2	7/8	22.2	27	275	500
H994912-500R	3/4	19.1	2	1-5/32	29.4	41	275	500
H994916-300R	1	25.4	2	1-7/16	36.5	64	275	300