

Hose

General Air & Water

 Refer to warnings and safety information on pages 3-4 and page 38.

Boston Industrial A/W



Tube: EPDM

Reinforcement: Fiber, 2 Braid

Cover: EPDM

Color: Red

Temperature Range: -40°F To +180°F

Type Of Branding: Ink Print

Working Pressure: 250-275 PSI

Type Of Coupling: 'U' Series, 430 'U', Barbed Inserts, Quick Acting, Long Shank, Series or Steel Nipple. Clamps—Interlocking, Bolt, Band or Wire.

Features:

- EPDM cover
- EPDM tube
- Braided reinforcement
- Continuous permanent brand
- Wide range of sizes

Advantages:

- Age, heat, and ozone resistant
- Heat resistant (limited oil resistance)
- Excellent coupling retention for impulse applications
- Easy identification
- For many applications

Markets:

- Agriculture
- Assembly/Manufacturers
- Construction
- Food Industry
- Metal Working
- Mining
- Oil Industry
- Paper/Pulp Industry
- Ship Building

Applications:

- Spraying and conveying water based liquid fertilizers and pesticides
- Transfer air and water; pneumatic tools

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	BRAID	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	STANDARD REELS (FT)
H181204-500R	1/4	6.3	2	19/32	15.1	16	275	500
H181205-500R	5/16	7.9	2	21/32	16.7	17	275	500
H181206-500R	3/8	9.5	2	23/32	18.3	19	275	500
H181208-500R	1/2	12.7	2	7/8	22.2	27	250	500
H181210-500R	5/8	15.9	2	1	25.4	36	250	500
H181212-500R	3/4	19.1	2	1-5/32	29.4	41	250	500
H181216-300R	1	25.4	2	1-7/16	36.5	46	250	300
H181220-300R	1-1/4	31.8	2	1-3/4	44.5	65	250	300
H181224-300R	1-1/2	38.1	2	2	50.8	82	250	300