


# Hose

## Cleaning Service Hoses

 Refer to warnings and safety information on pages 3-4 and page 53.

### Boston Pressure Washer



**Tube:** Nitrile RMA Class A Oil Resistance

**Reinforcement:** Wire, 1 Braid

**Cover:** Vinyl Nitrile MSHA Approved

**Color:** Blue

**Temperature Range:** -40°F To +200°F

**Type Of Branding:** Ink Print

**Working Pressure:** 3000 PSI

**Type Of Coupling:** 'M' Series

#### Features:

- Neoprene cover
- Nitrile tube
- Flexible one-wire braid

#### Advantages:

- Non-marking
- Abrasion, heat, ozone, and weather resistant
- Heat and detergent resistant
- Easy to handle at 3,000 PSI

#### Markets:

- Industrial Cleaning Markets
- Food Industry
- Construction Industry
- Marine
- Agricultural

#### Applications:

- Pressure wash engines, equipment, tanks, buildings, and roof cleaning, etc.
- Washdown of food processing facilities and equipment (not resistant to animal fats)
- High pressure cleaning and degreasing
- Boat cleaning
- Pressure wash engines, farm equipment, tanks and buildings

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	BRAID	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAX WORKING PRESS. (PSI)	M' SERIES NOM. CRIMP DIAMETER	STANDARD REELS (FT)
H34504	1/4	16.3	1	1/2	12.7	13	3,000	.630	50
H34504-100									100
H34504-250R									250
H34504-500R									500
H34506	3/8	9.5	1	5/8	15.9	18	3,000	.765	50
H34506-100									100
H34506-250R									250
H34506-500R									500
H34508	1/2	12.7	1	25/32	19.8	25	3,000	.915	50
H34508-100									100
H34508-250R									250
H34508-500R									500