

Hose

Cleaning Service Hoses

 Refer to warnings and safety information on pages 3-4 and page 53.

Boston Concord Sandblast



Tube: Natural Rubber

Reinforcement: Fiber, 2 Braid or 2 Ply

Cover: SBR

Color: Black

Temperature Range: -40°F To +150°F

Type Of Branding: Impression

Working Pressure: 100-150 PSI

Type Of Coupling: Sandblast Couplings that attach to O.D. of hose.

Features:

- SBR cover
- Continuous, natural rubber tube
- Conductive tube
- Continuous permanent brand
- Flexible

Advantages:

- Abrasion, age and weather resistant
- Abrasion resistant
- Static dissipating
- Easy identification
- Easy to handle

Markets:

- Construction Industry
- Metal Working
- Ship Building

Applications:

- Conveys sand from sandblast equipment to clean steel or concrete before painting or sealing
- Conveys sand or shot for cleaning purposes

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	REINF.	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	STANDARD LENGTH (FT)
H003408	1/2	12.7	2 Br	1-1/16	27.0	40	150	50
H003408-100								100
H003408-150								150
H003412	3/4	19.1	2 Br	1-1/2	38.1	70	150	50
H003412-100								100
H003412-150								150
H003416	1	25.4	2 Br	1-15/16	49.2	110	150	50
H003416-100								100
H003416-150								150
H003420	1-1/4	31.8	2 Ply	2-5/32	54.8	130	125	50
H003420-100								100
H003420-150								150
H003424	1-1/2	38.1	2 Ply	2-25/64	60.7	140	100	50
H003424-100								100
H003424-150								150
H003432	2	50.8	2 Ply	2-7/8	73.0	174	100	50
H003432-150								150