


Hose

Discharge

 Refer to warnings and safety information on pages 3-4 and page 57.

Boston Leader Water Discharge



Tube: EPDM
Reinforcement: Fiber, 2 or 4 Spiral, 2 Ply
Cover: EPDM
Color: Black
Temperature Range: -10°F To +150°F
Type Of Branding: Impression
Working Pressure: 80-150 PSI
 3:1 Safety Factor
Type Of Coupling: Cam and Groove, Combination Nipple.
 Clamps—Double Bolt or Band.

Features:

- EPDM cover
- EPDM tube
- Continuous permanent brand
- Available in longer lengths

Advantages:

- Abrasion and weather resistant
- Resistant to diluted chemicals
- Easy identification
- Economical; less waste

Markets:

- Construction
- Equipment Rental
- Mining
- Ship Building
- Tank Truck
- Agricultural

Applications:

- Water discharge
- Heavy duty with 150 PSI
- Mild chemicals only

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	REINF.	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	STANDARD LENGTH (FT)
Light Duty								
H030724-100	1-1/2	38.1	2 Sp	1-13/16	46.0	57	100	100
H030732-100	2	50.8	2 Sp	2-5/16	58.7	73	100	100
H030740-150	2-1/2	63.5	2 Ply	2-7/8	73.0	90	100	150
H030748-100	3	76.2	2 Sp	3-13/32	84.1	110	100	100
H030764-100	4	101.6	2 Sp	4-13/32	109.5	145	100	100
H030780-150	5	127.0	2 Ply	5-3/8	136.5	179	100	150
H030796-150	6	152.4	2 Ply	6-3/8	161.9	214	80	150
H03078A-150	8	203.2	2 Ply	8-25/64	213.1	283	80	150
Heavy Duty								
H037924-100	1-1/2	38.1	4 Sp	21/16	52.4	64	150	100
H037932-100	2	50.8	4 Sp	2-9/16	65.1	85	150	100
H037940-150	2-1/2	63.5	2 Ply	2-29/32	73.8	104	150	150
H037948-100	3	76.2	4 Sp	3-9/16	90.5	123	150	100
H037964-100	4	101.6	4 Sp	4-9/16	115.9	161	150	100
H037980-150	5	127.0	2 Ply	5-13/32	137.3	207	150	150
H037996-150	6	192.4	2 Ply	6-29/64	163.9	255	150	150
H03798A-150	8	203.2	2 Ply	8-13/32	213.5	313	100	150