

# Hose

## Discharge

 Refer to warnings and safety information on pages 3-4 and page 57.

### Boston Flexbilt K-50 Water Discharge



**Tube & Cover:** Polyvinyl Chloride (PVC)

**Reinforcement:** Woven Synthetic Yarn

**Color:** Blue

**Temperature Range:** -10°F To +150°F

**Type Of Branding:** Impression

**Working Pressure:** 35-75 PSI

**Type Of Coupling:** Cam and Groove, Water Suction, or Combination Nipple.  
Clamps—Double Bolt, Band or Wire.

#### Features:

- PVC construction
- Soft wall
- Smooth cover

#### Advantages:

- Light weight
- Abrasion resistant
- Folds flat for easy storage
- Easy to move
- Easy to clean

#### Markets:

- Construction
- Equipment Rental
- Mining

#### Applications:

- Open-end water discharge

PRODUCT NUMBER	NOMINAL I.D. (IN.)	I.D. (MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	STANDARD LENGTH (FT)
H050024-300	1-1/2	38.1	17	75	300
H050032-300	2	50.8	22	60	300
H050040-300	2-1/2	63.5	29	60	300
H050048-300	3	76.2	40	50	300
H050064-300	4	101.6	53	45	300
H050096-300	6	152.4	82	35	300

*Stated working pressures are tested at 70°F. Working pressure decreases as temperature increases. See chart on page 14 showing the relationship the relationship between working pressure and temperature for reinforced PVC hose.*