


Hose

General Purpose

 Refer to warnings and safety information on pages 3-4 and page 57.

Boston Contrac-Force



Tube: Polyvinyl Chloride (PVC)
Reinforcement: Fiber, 2 Spiral
Cover: Polyvinyl Chloride (PVC)
Color: Black
Temperature Range: -15°F To +150°F
Type Of Branding: Ink Print
Working Pressure: 150 PSI
 3:1 Safety Factor
Type Of Coupling: Machined brass hex head GHT.

Features:

- Light weight & flexible
- PVC tube and cover
- Continuous permanent brand
- Factory tested to exceed minimum electrical resistivity of one megohm per inch at 1000 volts D.C.

Advantages:

- Easy to handle and route
- Abrasion, age and ozone resistant
- Easy Identification

Markets:

- Construction

Applications:

- Water transfer and washdown

PRODUCT NUMBER	NOMINAL I.D. (IN.)	NOMINAL I.D. (MM)	SPIRAL	NOMINAL O.D. (IN.)	NOMINAL O.D. (MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	MTO* MIN. ORDER QTY.	STANDARD LENGTH (FT)
H171910-50C	5/8	15.9	2	53/64	21.0	18	150	100 pieces	5-50's
H171910-500								5,000	500
H171912-50C	3/4	19.1	2	1-3/64	26.6	24	150	—	5-50's
H171912-500								5,000	500

Stated working pressures are tested at 70°F. Working pressure decreases as temperature increases. See chart on page 14 showing the relationship between working pressure and temperature for reinforced PVC hose.

*MTO - Made to Order