


Hose

General Purpose

 Refer to warnings and safety information on pages 3-4 and page 57.

Boston Contractors Water



Tube: EPDM

Reinforcement: Fiber, 2 Spiral

Cover: EPDM/Pinpricked

Color: Black

Temperature Range: -30°F To +160°F

Type Of Branding: Ink Print

Working Pressure: 150 PSI
3:1 Safety Factor

Type Of Coupling: Machined brass hex head GHT.
Short Shank or Barbed Inserts.
Clamps—Brass Collar, Single Bolt or Band.

Features:

- EPDM cover
- EPDM tube
- Continuous permanent brand

Advantages:

- Abrasion, age, heat, and weather resistant
- Heat resistant
- Easy identification

Markets:

- Construction

Applications:

- Water transfer and washdown

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	SPIRAL	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	STANDARD LENGTH (FT)
H198710	5/8	15.9	2	15/16	24.6	23	150	50
H198710-600R								600
H198712	3/4	19.1	2	1-3/32	28.6	30	150	50
H198712-600R								600
H198710-50C	5/8	15.9	2	15/16	24.6	23	150	5-50's
H198712-50C	3/4	19.1	2	1-3/32	28.6	30	150	5-50's