


Hose

Dry Bulk Transfer

 Refer to warnings and safety information on pages 3-4 and page 66.

Boston Lynx HD Softwall Dry Material



Tube: Natural Rubber/SBR Blend (1/4" tube thickness)
Static Dissipating

Reinforcement: Fiber, 2 Spiral

Cover: SBR

Color: Black

Temperature Range: -10°F To +150°F

Type Of Branding: Printed Strip

Working Pressure: 50 PSI (Depending on coupling)

Type Of Coupling: Cam and Groove, or Combination
Nipple. Clamps—Band.

Features:

- SBR cover
- Natural rubber/SBR blend tube 1/4" thick
- Conductive tube
- Continuous printed brand
- Available in longer lengths
- Soft wall hose

Advantages:

- Abrasion, age and weather resistant
- Static dissipating
- Easy identification
- Economical; less waste
- Folds flat for easy storage

Markets:

- Tank Truck
- In-plant Transfer
- Bottling Plant
- Coal Plant

Applications:

- Transfer of dry bulk (cement, sand, lime, etc.); discharge of any abrasive materials
- Transfer of bottle caps
- Transfer of cleaning agents

PRODUCT NUMBER	NOMINAL I.D.		SPIRAL	NOMINAL O.D.		APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	MTO* MIN. ORDER QTY.	STANDARD LENGTH (FT)
	(IN.)	(MM)		(IN.)	(MM)				
H052164-100	4	101.6	2	4-13/16	122.2	300	50	500	100
H052180-150	5	127	2	5-7/8	149.2	320	50	—	150

*MTO - Made to Order