


Hose

Dry Bulk Transfer

 Refer to warnings and safety information on pages 3-4 and page 66.

Boston Sabertooth Dry Material



Tube: Natural Rubber/SBR Blend
Static Dissipating

Reinforcement: Fiber, 4 Spiral and Helical Wire

Cover: SBR

Color: Black

Temperature Range: -10°F To +160°F

Type Of Branding: Printed Strip

Suction: Full Vacuum

Working Pressure: 100 PSI (Depending on coupling)

Type Of Coupling: Cam and Groove, or Combination Nipple. Clamps—Band.

Features:

- SBR cover
- Natural rubber/SBR blend tube
- Conductive tube
- Continuous printed brand
- Available in longer lengths

Advantages:

- Abrasion, age and weather resistant
- Static dissipating
- Easy identification
- Economical; less waste

Markets:

- Tank Truck
- In-plant Transfer
- Bottling Plant
- Coal Plant

Applications:

- Transfer of dry bulk (cement, sand, lime, plastics, animal feed, etc.); suction/discharge of any abrasive materials
- Transfer of bottle caps
- Transfer of cleaning agents

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	SPIRAL	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	MIN. BEND RADIUS (IN.)	(MM)	STANDARD LENGTH (FT)
H034748-100	3	76.2	4	4	101.6	320	100	9	228.6	100
H034764-100	4	101.6	4	5	127.0	440	100	11	279.4	100