


Hose

Specialty Service Hoses

 Refer to warnings and safety information on pages 3-4 and page 71.

Boston Nitrogen Service



Tube: Nitrile
Reinforcement: Fiber, 4 Spiral
Cover: Neoprene/Pinpricked
Color: Yellow (YW), Blue (BU)
Temperature Range: Ambient (70°F)
Type Of Branding: Ink Print
Working Pressure: 300 PSI
Type Of Coupling: 'U' Series, Barbed Inserts, Long Shank. Clamps—Interlocking, Band.

Features:

- Neoprene cover
- Nitrile tube
- Continuous permanent brand
- Flexible

Advantages:

- Abrasion, age, and oil resistant
- Abrasion and oil resistant
- Easy identification
- Easy to handle

Markets:

- Chemical/Petroleum Industry

Applications:

- Transfer of nitrogen at ambient temperatures

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	SPIRAL	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	MTO* MIN. ORDER QTY.	STANDARD LENGTH (FT)
H881108-250	1/2	12.7	4	7/8	22.2	23	300	40 pieces	5-50's(YW)
H881112-250	3/4	19.1	4	1-3/16	30.2	38	300	—	5-50's(YW, BU)
H881112-600R									600 (BU)

*MTO - Made to Order