


Hose

Specialty Service Hoses

 Refer to warnings and safety information on pages 3-4 and page 71.

Boston Kelly Power



Tube: Nitrile (RMA Class A)
Reinforcement: Wire, 4 Spiral
Cover: Neoprene
Color: Black
Temperature Range: -40°F to +250°F
Type Of Branding: Printed Strip
Working Pressure: 3000 PSI
 4:1 Safety Factor
Type Of Coupling: 430 'U' Series.

Features:

- Neoprene cover
- Neoprene tube
- Patch brand

Advantages:

- Abrasion, oil and weather resistant
- Good oil resistance
- Easy identification

Markets:

- Oil Exploration
- Drilling

Applications:

- Rotary drilling on portable drilling rigs, work over rigs, and slim hole rigs

PRODUCT NUMBER	NOMINAL I.D. (IN.)	NOMINAL I.D. (MM)	SPIRAL	NOMINAL O.D. (IN.)	NOMINAL O.D. (MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	MINIMUM BEND RADIUS (IN.)	MINIMUM BEND RADIUS (MM)	STANDARD LENGTH (FT)
H037732	2	50.8	4	2-21/32	67.5	310	3,000	25	635	50*

*150's available on request.