


Hose

Specialty Service Hoses

 Refer to warnings and safety information on pages 3-4 and page 71.

Boston Nyall



Tube: Nylon

Reinforcement: Fiber, 1 or 2 Braid

Cover: Neoprene (BK), Vinyl Nitrile (RD)

Red—RMA Class B Oil Resistance

Color: Black (BK), Red (RD)

Temperature Range: -30°F to +160°F

Type Of Branding: Ink Print

Working Pressure: 500-750 PSI

Type Of Coupling: 'U' Series, Barbed Inserts, Quick Acting or Steel Nipple. Clamps—Interlocking, Band.

Features:

- Neoprene cover
Vinyl Nitrile cover
- Nylon tube
- Continuous permanent brand
- High working pressure multi-purpose hose

Advantages:

- Abrasion, oil and weather resistant
- Compatible with many fluids (See Chemical Resistance Chart)
- Excellent flow rate
- No swelling
- Easy to clean
- Easy identification
- Wide variety of applications

Markets:

- Agriculture
- Equipment Rental
- Assembly/Manufacturers
- Chemical/Petroleum Industry
- Lumber/Paper/Pulp Industry
- Food Processing Industry
- Construction
- Ship Building

Applications:

- Fertilizer and pesticides spray
- General service application; convey air, water, oils, paints, etc.
- Transfer of chemicals, solvents, paints, glues, and petroleum products (See Chemical Resistance Chart)
- Paint spray
- Convey air, water, and fuels; paint spray

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	BRAID	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	STANDARD REELS (FT)
H194104-500R	1/4	6.3	1	1/2	12.7	10	500	500(RD, BK)
H194105-500R	5/16	7.9	1	9/16	14.3	13	500	500(BK)
H194106-500R	3/8	9.5	1	11/16	17.5	15	500	500(RD, BK)
H194108-500R	1/2	12.7	1	25/32	19.8	19	500	500(RD)
H194208-500R	1/2	12.7	2	7/8	22.2	26	750	500(RD, BK)
H194212-500R	3/4	19.1	2	1-3/16	30.2	40	750	500(RD)
H194216-300R	1	25.4	2	1-1/2	38.1	56	500	300(RD)