


Hose

Specialty Service Hoses

 Refer to warnings and safety information on pages 3-4 and page 71.

Boston Boston Blackcat Hot Tar & Asphalt Corrugated



Tube: Nitrile
Reinforcement: 2 Fiberglass Plys and Helical Wire
Cover: Neoprene
Color: Black
Temperature Range: +350°F
Type Of Branding: Printed Strip
Suction: Full Vacuum
Working Pressure: 200 PSI (Depending on Coupling)*
Type Of Coupling: Cam and Groove, Combination Nipple, or Swaged/Crimped. Clamps—Interlocking or Band (only for pressures up to 50 PSI).

Features:

- Neoprene cover
- Nitrile tube
- Continuous printed brand and caution label every ten feet
- Fiberglass braid

Advantages:

- Abrasion, oil and weather resistant
- Heat and oil resistant
- Handles intermittent temperatures of hot tar up to +400°F
- Light weight
- Easy to handle
- Longer life
- Easy identification
- Assures proper use

Markets:

- Tank Trucks
- Construction
- Oil Field
- Manufacturing Plants

Applications:

- Loading or unloading, pumping, suction, or gravity flow discharge; transfer of hot tar
- Transfer of asphalt in roofing shingle plant

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	PLY	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	MINIMUM BEND RADIUS (IN.)	(MM)	STANDARD LENGTH (FT)
H061632	2	50.8	2	3	76.2	234	200	5	127	50
H061632-100										100
H061632-150										150

Handles intermittent temperature of hot tar and asphalt up to +400°F.

**Please contact Eaton Technical Support for applications at continuous elevated temperatures above 250°F.*