


Hose

Specialty Service Hoses

 Refer to warnings and safety information on pages 3-4 and page 71.

Boston Bulldog Fuel Oil Delivery



Tube: Nitrile (RMA Class A)
Reinforcement: Fiber, 2 Braid
Cover: Vinyl Nitrile
Color: Red
Temperature Range: -40°F to +180°F
Type Of Branding: White Ink Print
Working Pressure: 250 PSI
Type Of Coupling: Internally Expanded Permanent Petroleum Couplings or Reattachable Fuel Oil Couplings

Features:

- Neoprene cover
- Nitrile tube
- Continuous printed brand and caution label every ten feet
- Fiberglass braid

Advantages:

- Abrasion, oil and weather resistant
- Heat and oil resistant
- Handles intermittent temperatures of hot tar up to +400°F
- Light weight
- Easy to handle
- Longer life
- Easy identification
- Assures proper use

Markets:

- Tank Trucks
- Construction
- Oil Field
- Manufacturing Plants

Applications:

- Loading or unloading, pumping, suction, or gravity flow discharge; transfer of hot tar
- Transfer of asphalt in roofing shingle plant

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	BRAID	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 (FT)	MAXIMUM WORKING PRESS. (PSI)	STANDARD LENGTH (FT)
H90120-150	1-1/4	31.8	2	1-3/4	44.5	65	250	150
H90122-150	1-3/8	34.9	2	1-55/64	47.0	75	250	150
H90124-150	1-1/2	38.1	2	2	50.8	85	250	150