


Hose

Acid Suction

 Refer to warnings and safety information on pages 3-4 and pages 93-94.

Boston Cheetah Acid Suction



Tube: Hypalon®
Reinforcement: Fiber, 2 Ply and Helical Wire
Cover: Neoprene
Color: Yellow
Temperature Range: -40°F to +200°F
Type Of Branding: Printed Strip
Suction: Full Vacuum
Working Pressure: 150 PSI (Depending on coupling)
Type Of Coupling: Cam and Groove or Swaged/Crimped. Clamps—Interlocking or Band.

Features:

- Neoprene cover
- Hypalon tube
- Continuous printed brand
- Yellow cover
- Flexible
- Transfer of acids and chemicals

Advantages:

- Age, chemical and ozone resistant; longer hose life.
- Acid and chemical resistant
- Easy identification
- Meets OSHA color requirements for flexible pipe systems
- Easy to handle
- Flexibility of applications

Markets:

- Chemical Industry
- Lumber/Woodworking
- Plywood Mfg.
- Pulp Processing
- Tank Truck
- Railroad Tank Car
- Metal Working

Applications:

- Transfer of acids and chemicals through pumping, suction, and discharge.
- Transfer of chemicals for processing products.
- Loading and unloading, pumping, or gravity flow discharge
- Etching; cleaning.

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	PLY	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	MINIMUM BEND RADIUS (IN.)	(MM)	STANDARD LENGTH (FT)
H042324-150	1-1/2	38.1	2	2-3/8	60.3	155	150	6	152.4	150
H042332-150	2	50.8	2	2-7/8	73.0	192	150	9	228.6	150
H042348-150	3	76.2	2	3-15/16	100.0	286	150	20	508.0	150
H042364-150	4	101.6	2	4-15/16	125.4	369	150	30	762.0	150

Hypalon® is a registered trademark of DuPont Dow Elastomers.