


Hose

Chemical Transfer

 Refer to warnings and safety information on pages 3-4 and pages 93-94.

Boston Green Cross-Link



Tube: Clear Cross-Linked Polyethylene (XLPE)
Reinforcement: Fiber, 2 Braid or 2 Ply and Helical Wire
Cover: EPDM
Color: Green
Temperature Range: -45°F to +150°F
Type Of Branding: Impression
 Suction: Full Vacuum
Working Pressure: 150-200 PSI (Depending on coupling)
Type Of Coupling: Cam and Groove or Swaged/Crimped. Clamps—Interlocking or Band.

Features:

- EPDM cover
- Clear cross-linked polyethylene tube
- Continuous impression brand
- Green cover
- Smooth bore
- Serialized lengths

Advantages:

- Chemical and ozone resistant; longer hose life.
- Chemical, petroleum, and solvent resistant; won't contaminate, or discolor fluids
- Easy identification
- Rapid fluid flow
- Easy to clean
- Safety and maintenance records

Markets:

- Chemical/Petroleum Industry
- Lumber/Woodworking
- Plywood Mfg.
- Pulp/Paper Processing
- Tank Truck
- Railroad Tank Car
- Waste Hauling

Applications:

- Transfer of acids, chemicals, solvents, and petroleum products.
- Transfer of chemicals and solvents for processing products.
- Loading and unloading, pumping, suction, or gravity flow discharge

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	REINF.	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	MINIMUM BEND RADIUS (IN.)	(MM)	STANDARD LENGTH (FT)
H037816-150	1	25.4	2 Br	1-17/32	38.9	72	200	5	127.0	150
H037820-150	1-1/4	31.8	2 Ply	1-7/8	47.6	86	200	8	203.2	150
H037824-150	1-1/2	38.1	2 Ply	2-1/8	54.0	89	200	8	203.2	150
H037832-150	2	50.8	2 Ply	2-5/8	66.7	113	200	9	228.6	150
H037848-150	3	76.2	2 Ply	3-5/8	92.1	164	150	16	406.4	150
H037864-150	4	101.6	2 Ply	4-11/16	119.1	239	150	21	533.4	150