


Hose

Chemical Transfer

 Refer to warnings and safety information on pages 3-4 and pages 93-94.

Boston Marauder



Tube: Modified Ultrahigh Molecular Weight Polyethylene (U.H.M.W.) FDA Approved Materials

Reinforcement: Fiber, 2 Ply and Helical Wire

Cover*: EPDM (H0683 Modified U.H.M.W. available with 900 ft minimum order)

Color: Blue & Green (other colors available with 900 ft minimum order)

Temperature Range: -45°F to +250°F (depends on media being transferred, please contact technical support at 1-888-258-0222 for temperatures above 160°F)

Type Of Branding: Printed Strip

Working Pressure: 200 PSI (depends on coupling)

Type Of Coupling: Cam and Groove or Swaged/Crimped.

Clamps: Interlocking or Band.

*Modified U.H.M.W. cover wrap for superior abrasion resistance available with 900 ft minimum order.

Features:

- Superior flexibility
- Tight bend radius
- Light weight
- Easy to clean
- Available with modified U.H.M.W. cover wrap for superior abrasion resistance
- FDA approved materials

Advantages:

- 40% less force to bend than Corrugated Chemcat
- Chemical, petroleum and solvent resistant.
- Abrasion, chemical and ozone resistant.

Markets:

- Bulk Hauling
- Barges
- Tank Trucks
- Railroad Tank Cars
- In-plant Transfer
- Transportation
- Mixing Operations
- Chemical Handling

Applications:

- Loading and unloading, pumping, suction, or gravity flow discharge
- Transfer of acids, chemicals and solvents.
- Food Transfer

CATALOG NUMBER	NOMINAL I.D.		PLY	NOMINAL O.D.		APPROX. WEIGHT (LBS) PER 100 FT	MAX. WORKING PRESS. (PSI)	MIN. BEND RADIUS (IN)	STANDARD LENGTHS (FT)
	(IN)	(MM)		(IN)	(MM)				
H068132	2	50.8	2	2-5/8	67.0	116	200	5	150(GR,BU)
H068140	2-1/2	63.5	2	3-1/8	79.4	142	200	6	150(GR,BU)
H068148	3	76.2	2	3-5/8	92.2	168	200	6.5	150(GR,BU)