


Hose

Hot Liquid Transfer

 Refer to warnings and safety information on pages 3-4 and pages 93-94.

Boston Alleycat



Tube: Synthetic Rubber Specially Compounded for High Temperature Applications

Reinforcement: Wire Braid, 2 Stainless Steel Static Wires (1-1/2" and 2"). 2 Steel Helical Wires (3").

Cover: EPDM

Color: Yellow

Temperature Range: -40°F to +300°F

Type Of Branding: Printed Strip

Suction: Full Vacuum

Working Pressure: 500 PSI (Depending on coupling and clamp)

Type Of Coupling: Interlocking, Cam and Groove or Swaged/Crimped. Clamps—Interlocking, Swaged/Crimp Ferrule or Band.

Features:

- Wire braid
- Dual stainless steel static
- EPDM cover
- Specially compounded tube

Advantages:

- Permanent crush-resistant
- 500 psi in all sizes
- Abrasion, age- and ozone-resistant cover
- Handles up to 300°F
- May be cleaned with steam, open end discharge only
- Safe transfer of hot cleaning solution

Markets:

- Pulp and Paper Industry
- Industrial Cleaning

Applications:

- In-plant transfer of liquors and cleaning solutions
- Tank Spinner
- Hot Caustics

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	WIRE BRAID	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	MINIMUM BEND MTO MIN. RADIUS (IN.)	STANDARD ORDER QTY.	LENGTH (FT)
H969924	1-1/2	38.1	2	2-3/16	55.6	150	500	8	—	50
H969924-150										150
H969932	2	50.8	2	2-11/16	68.3	177	500	16	—	50
H969932-150										150
H969948	3	76.2	2	3-23/32	94.5	300	500	24	2850	50
H969948-150										150