


Hose

Light Duty Petroleum

 Refer to warnings and safety information on pages 3-4 and page 109.

Boston Bobcat LT Light Weight Petroleum



Tube: Vinyl Nitrile

Reinforcement: Fiber, 2 Ply and Helical Wires

Cover: Vinyl Nitrile (RD), Neoprene (BK)

Color: Red (RD) or Black (BK)

Temperature Range: -40°F to +180°F

Type Of Branding: Printed Strip

Suction: Full Vacuum

Working Pressure: 100 PSI (Depending on coupling and clamps)

Type Of Coupling: Cam and Groove, Combination Nipple or Swaged/Crimped. Clamps—Band.

Features:

- Vinyl nitrile cover
- Vinyl nitrile tube
- Continuous printed brand with caution label every ten feet
- Light weight and flexible

Advantages:

- Abrasion, oil and weather resistant
- Easy identification
- Safety
- Easy to route; easy to handle

Markets:

- Petrochemical/Petroleum Industry
- Oil Exploration and Drilling
- Tank Trucks
- Gasoline Drop
- Waste Hauling

Applications:

- Transfer and blending of petroleum products
- Transfer of crude oil, salt water, fresh (non-potable) water, and slurries.
- Loading or unloading, pumping, suction, or gravity flow discharge

CATALOG NUMBER	NOMINAL I.D. (IN)	(MM)	PLY	NOMINAL O.D. (IN)	(MM)	APPROX. LBS. WEIGHT PER 100 FT	MAXIMUM WORKING PRESS. (PSI)	MINIMUM BEND RADIUS (IN.)	(MM)	STANDARD LENGTHS (FT)
H036932-150	2	50.8	2	2-1/2	63.5	119	100	3	76.2	150 (RD,BK)
H036948-150	3	76.2	2	3-1/2	88.9	188	100	5	127.0	150 (RD,BK)
H036964-150	4	101.6	2	4-1/2	114.3	240	100	7	177.8	150 (RD,BK)
H036832-150	2	50.8	2	2-1/2	63.5	119	150	3	76.2	150 (RD,BK)
H036848-150	3	76.2	2	3-1/2	88.9	188	150	5	127.0	150 (RD)