


Hose

Medium Duty Petroleum

 Refer to warnings and safety information on pages 3-4 and page 109.

Boston Puma Petroleum



Tube: Vinyl Nitrile

Reinforcement: Fiber, 2 Braid, 2 or 4 Ply and Helical Wires

Cover: Vinyl Nitrile

Color: Red (RD) or Black (BK)

Temperature Range: -40°F to +180°F

Type Of Branding: Printed Strip

Suction: Full Vacuum

Working Pressure: 150 PSI (Depending on coupling and clamps)

Type Of Coupling: Cam and Groove, Combination Nipple or Swaged/Crimped. Clamps—Band.

Features:

- Vinyl nitrile cover
- Vinyl nitrile tube
- Continuous printed brand

Advantages:

- Abrasion, animal fat, oil and weather resistant
- Easy identification

Markets:

- Petrochemical/Petroleum Industry
- Paper/Pulp Industry
- Oil Exploration and Drilling
- Ship Building
- Tank Trucks
- Railroad Tank Cars
- Waste Hauling

Applications:

- Transfer of petroleum products
- Transfer of crude oil, salt water, fresh (non-potable) water, and slurries.
- Loading or unloading, pumping, suction, or gravity flow discharge

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	REINF.	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	MINIMUM BEND RADIUS (IN.)	(MM)	STANDARD LENGTH (FT)*
H036316-150	1	25.4	2 Ply	1-31/64	37.7	75	150	6	152.4	150(BK)
H036320-150	1-1/4	31.8	2 Ply	1-25/32	45.2	85	150	6	152.4	150(BK)
H036324-50										50
H036324-100	1-1/2	38.1	4 Sp	2-1/16	52.4	98	150	5	127.0	100(BK)
H036324-150										150
H036332-50										50
H036332-100	2	50.8	4 Sp	2-9/16	65.1	115	150	6	152.4	100(BK,RD)
H036332-150										150
H036340-150	2-1/2	63.5	2 Ply	3-1/32	77.0	140	150	9	228.6	150(BK)
H036348-100	3	76.2	4 Sp	3-9/16	90.5	166	150	12	304.8	100(BK,RD)
H036364-50										50
H036364-100	4	101.6	4 Sp	4-9/16	115.9	224	150	14	355.6	100(BK)
H036364-150										150
H036396-25	6	152.4	2 Ply	6-55/64	174.2	514	150	30	762.0	25(BK)
H036396-100										100(BK)
H036396-150										150(BK)
H03638A-25	8	203.2	4 Ply	8-55/64	225.0	674	150	—	—	25(BK)
H03638A										50(BK)

*150 foot lengths available upon request.