


# Hose

## Steam Service Hose

 Refer to warnings and safety information on pages 3-4 and pages 115-118.

### Boston Concord 250 O.R.



**Tube:** EPDM

**Reinforcement:** Wire, 2 Braid

**Cover:** Special Oil Resistant Compound/Pinpricked

**Color:** Black (BK) or Red (RD)

**Temperature Range:** +450°F

**Type Of Branding:** Ink Print

**Working Pressure:** 250 PSI (Depending on coupling)  
10:1 Safety Factor

**Type Of Coupling:** Boston Wolf Permanent Crimp Couplings or Interlocking. Clamps—Interlocking, (2 Bolt, 4 Bolt).

#### Features:

- Special cover
- EPDM tube
- Continuous ink print and date code
- Minimum 10-to-1 safety factor
- Date code

#### Advantages:

- Oil resistant.
- Excellent heat resistance
- Handles most steam cleaning detergents
- Easy identification
- Meets safety standards of RMA
- Safety & maintenance records

#### Markets:

- Chemical/Petroleum Industry
- Industrial Cleaning Markets
- Ship Building
- Food Industry
- Lumber/Woodworking
- Plywood Mfg./Cardboard
- Pulp Processing

#### Applications:

- Transfer of steam for processing products and cleaning equipment
- Transfer of steam or hot 200°F detergent-type solutions for cleaning of equipment, tanks, buildings, etc.
- Transfer of steam to melt glues, waxes, etc.

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	BRAID	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT	MAXIMUM WORKING PRESS. (PSI)	MTO* MIN. ORDER QTY.	STANDARD LENGTH (FT)
H968208	1/2	12.7	2	1-1/32	26.2	46	250	3000	50(BK,RD)
H968212	3/4	19.1	2	1-11/32	34.1	70	250	3000	50(BK,RD)
H968216	1	25.4	2	1-9/16	39.7	96	250	3000	50(BK,RD)

*Not to be used as a pressure washer hose*

*\*MTO - Made to Order*