


Hose

Steam Service Hose

 Refer to warnings and safety information on pages 3-4 and pages 115-118.

Boston Concord Standard Steam & Concord Standard Steam-Spiral Stripe



Tube: Patrex (Chlorobutyl)

Reinforcement: Wire, 2 Braid, 2 Stainless Steel Static Wires

Cover: EPDM/Pinpricked

Color: Black (BK), Black and Red Stripe (RD)

Temperature Range: +450°F

Type Of Branding: Impression

Working Pressure: 250 PSI (Depending on coupling)
10:1 Safety Factor

Type Of Coupling: Interlocking.
Clamps—Interlocking, (2 Bolt, 4 Bolt).

Features:

- EPDM cover
- Patrex (Chlorobutyl) tube
- Continuous impression brand and date code
- Minimum 10-to-1 safety factor
- Built in separate static wire
- Barber pole striped cover (RD)

Advantages:

- Heat, age, ozone and weather resistant.
- Excellent heat resistance
- Handles most steam cleaning detergents
- Easy identification
- Safety & maintenance records
- Meets safety standards of RMA
- Assures safe grounding
- Safety
- Color code system

Markets:

- Chemical/Petroleum Industry
- Industrial Cleaning Markets
- Ship Building
- Lumber/Woodworking
- Plywood Mfg./Cardboard
- Pulp Processing

Applications:

- Transfer of steam for processing products and cleaning equipment
- Transfer of steam or hot 200°F detergent-type solutions for cleaning of equipment, tanks, buildings, etc.
- Transfer of steam to melt glues, waxes, etc.

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	BRAID	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT	MAXIMUM WORKING PRESS. (PSI)	STANDARD LENGTH (FT)*
H008408	1/2	12.7	2	1-1/8	28.6	55	250	50(BK,RD)
H008412	3/4	19.1	2	1-3/8	34.9	78	250	50(BK,RD)
H008416	1	25.4	2	1-5/8	41.3	100	250	50(BK,RD)
H008420	1-1/4	31.8	2	1-15/16	49.2	135	250	50(BK,RD)
H008424	1-1/2	38.1	2	2-3/16	55.6	155	250	50(BK,RD)
H008432	2	50.8	2	2-11/16	68.3	194	250	50(BK,RD)

Not to be used as a pressure washer hose

** 225 - 295 foot reels available as Made to Order*