


Couplings

General Information

Single Bolt Clamp




Service: Low pressure, and suction service on shank couplings, combination nipples, and pipe nipples

Size Range: 7/8" to 5 1/4" hose O.D.

Description: Cast malleable iron, plated.

Attachment: Bolted on hose

Double Bolt Clamp



Service: Low or medium pressure, and suction service with large sizes of combination nipples, or couplings

Size Range: 3 1/2" to 17 1/2" hose O.D.

Description: Cast malleable iron, plated, and brass

Attachment: Applied over hose and bolted into position

Band Clamp




Service: Low or medium pressure, and suction service

Size Range: 3/4" to 6" hose O.D.

Description: Pre-formed flat stainless steel, high carbon steel

Attachment: Special locking band tool

Wire Hose Clamp



Service: Suitable for medium pressure, air, water or general purpose hose; good for hose with helical wire or corrugations; available in larger sizes for pin lug, serrated pipe nipple or combination nipples

Size Range: 5/8" to 13 1/4" hose O.D.

Description: Pre-formed round wire made of stainless steel, galvanized steel, copper, bronze or aluminum

Attachment: Wire ends pulled and crimped with special tool or machine

Brass Ferule



Service: Low or medium pressure air or water using general purpose hose and brass inserts

Size Range: 31/64" to 1 1/2" hose O.D.

Description: Made from various gauge brass tubing; stamped with Standard Industrial Part Number

Attachment: Crimped on using either ribbed or plain die