


Couplings

Coll-O-Crimp

'E' Series

Hose End Series: 'E' Series



Refer to important safety information found on pages 3-4 of this catalog.

Note: Refer to current price list for availability of cataloged items. Configurations and dimensions subject to change without notice.

Typical Application: General purpose low- and medium-pressure fluid transfer.

Compatible Hose: H265/Ultraforce, H275/Polyforce, H285/Clearforce

Pressure: Determined by maximum working pressure for hose size and hose end configuration whichever is lesser.

Material: AISI/SAE 12L14 carbon steel

Plating: Zinc; yellow dichromate finish

Advantages: Wide selection of hose and end configurations allowing for a diverse number of applications where hose compatibility is a problem.


Ordering Information: Order individually by catalog number.

Assembly Instructions: See Hose End & Tool Selector Chart for crimp specifications.

Assemble With: T-400-1, T-410-1, T-420-1, T-440-1, T-460, T-462, T-465-1, T480.

Label Set: FS-1200


Male Pipe Rigid



HOSE I.D.	PIPE SIZE	CATALOG NUMBER	THREAD SIZE	A	HOSE CUT-OFF FACTOR†	HOLE DIA.	HEX E
3/16	1/8	03E-102	1/8-27	1.58	.75	.09	7/16
3/16	1/4	03E-104	1/4-18	1.83	1.00	.09	9/16
1/4	1/8	04E-102	1/8-27	1.60	.75	.16	7/16
1/4	1/4	04E-104	1/4-18	1.79	1.00	.16	9/16
1/4	3/8	04E-106	3/8-18	1.82	1.00	.16	11/16
5/16	1/4	05E-104	1/4-18	1.86	.94	.22	9/16
5/16	3/8	05E-106	3/8-18	1.89	1.00	.22	11/16
3/8	1/4	06E-104	1/4-18	1.90	1.00	.27	9/16
3/8	3/8	06E-106	3/8-18	1.93	1.00	.27	11/16
3/8	1/2	06E-108	1/2-14	2.17	1.25	.27	7/8
1/2	3/8	08E-106	3/8-18	2.02	1.00	.38	3/4
1/2	1/2	08E-108	1/2-14	2.27	1.25	.38	7/8
3/4	3/4	12E-112	3/4-14	2.51	1.31	.61	1-1/16
1	1	16E-116	1-11-1/2	2.95	1.63	.84	1-3/8

Male Pipe Swivel

Note: Swivel for installation purposes only. (Not for temperatures above 200°F.)



HOSE I.D.	PIPE SIZE	CATALOG NUMBER	THREAD SIZE	A	HOSE CUT-OFF FACTOR†	HOLE DIA.	HEX E	HEX F
1/4	1/4	04E-J04	1/4-18	2.68	1.81	.16	5/8	13/16
5/16	1/4	05E-J04	1/4-18	2.75	1.81	.22	5/8	13/16
3/8	3/8	06E-J06	3/8-18	2.79	1.81	.27	11/16	7/8
1/2	1/2	08E-J08	1/2-14	3.03	2.00	.39	3/4	7/8
3/4	3/4	12E-J12	3/4-14	3.73	2.50	.61	1-1/4	1-1/4

†To determine the correct length of hose, subtract the cut-off factor for each end fitting from the overall length of assembly.