


Couplings

Coll-O-Crimp 'E' Series


SAE 37° Male Rigid



HOSE I.D.	TUBE SIZE	CATALOG NUMBER	THREAD SIZE	A	HOSE CUT-OFF FACTOR†	HOLE DIA.	HEX E
1/4	1/4	04E-504	7/16-20	1.78	.94	.16	1/2
1/4	5/16	04E-505	1/2-20	1.78	.94	.19	9/16
1/4	3/8	04E-506	9/16-18	1.82	1.00	.22	5/8
5/16	5/16	05E-505	1/2-20	1.86	.94	.22	9/16
3/8	3/8	06E-506	9/16-18	1.92	1.00	.22	5/8
3/8	1/2	06E-508	3/4-16	2.08	1.19	.33	13/16
1/2	1/2	08E-508	3/4-16	2.18	1.19	.38	13/16
1/2	5/8	08E-510	7/8-14	2.31	1.25	.42	15/16
3/4	3/4	12E-512	1-1/16-12	2.63	1.44	.61	1-1/8
1	1	16E-516	1-5/16-12	2.83	1.50	.84	1-3/8

SAE 37° Female Swivel

(Exceptions Noted, Refer to Footnotes)



HOSE I.D.	TUBE SIZE	CATALOG NUMBER	THREAD SIZE	A	HOSE CUT-OFF FACTOR†	HOLE DIA.	HEX E	HEX F
3/16	1/4	03E-604 ^a	7/16-20	1.89	1.00	.09	7/16	9/16
1/4	1/4	04E-604 ^a	7/16-20	1.92	1.13	.16	7/16	9/16
1/4	5/16	04E-605 ^a	1/2-20	2.00	1.19	.16	1/2	5/8
1/4	3/8	04E-606 ^c	9/16-18	2.06	1.25	.16	9/16	11/16
5/16	5/16	05E-605 ^a	1/2-20	2.07	1.19	.22	1/2	5/8
5/16	3/8	05E-406 ^b	5/8-18	2.03	1.13	.22	9/16	3/4
5/16	3/8	05E-606 ^c	9/16-18	2.12	1.19	.22	9/16	11/16
3/8	3/8	06E-406 ^b	5/8-18	2.06	1.13	.27	9/16	3/4
3/8	3/8	06E-606 ^c	9/16-18	2.19	1.25	.27	9/16	11/16
3/8	1/2	06E-608 ^a	3/4-16	2.30	1.38	.27	3/4	7/8
1/2	1/2	08E-608 ^a	3/4-16	2.39	1.38	.38	3/4	7/8
1/2	5/8	08E-610 ^a	7/8-14	2.51	1.50	.38	7/8	1
3/4	3/4	12E-412 ^b	1-1/16-14	2.76	1.56	.61	1	1-1/4
3/4	3/4	12E-612 ^c	1-1/16-12	2.76	1.56	.61	1	1-1/4
1	1	16E-616 ^c	1-5/16-12	3.05	1.75	.84	1-1/4	1-1/2

†To determine the correct length of hose, subtract the cut-off factor for each end fitting from the overall length of assembly.

a Swivel nuts are universal

b both SAE 37° and 45° connections.

c SAE 37° flare connection only.