


Equipment

Coll-O-Crimp Portable T-480

 Refer to safety information regarding Coll-O-Crimp hose, hose fittings and assembly equipment compatibility on pages 3-4.

T-480-HP



Refer to pages 170 through 178 for Coll-O-Crimp tooling, tooling packages and pumps.

Refer to safety information regarding Coll-O-Crimp crimping procedures on page 158.

Make factory-type hose assemblies anywhere-anytime! Versatile and portable, this package offers the ease of use you are looking for in a Coll-O-Crimp hose assembly system. The T-480 Coll-O-Crimp Press packages are offered in four options. Listed below are press/power unit packages.

For cabinets see pages 183-184 (not included).

T-480-HP • Portable Coll-O-Crimp Press & Hand Pump Package

Capacity: 3/16" I.D. 1 fiber braid through 1-1/4" I.D. 6 spiral hose-

Mounting: Free Standing Base

Size: 22-1/2" high, 14" long, 10-1/2" wide

Total Weight: 112 lbs.

Pump Specifications:

Dimensions: 7-3/16" high, 22" long, 4-3/4" wide

Pressure: 0-10,000 psi

Outlet Port Size: 3/8" NPT


Hydraulic Oil: Enerpac

Reservoir Capacity: 55 cu. in.

Includes T-480-68 blue pusher extension ring. Refer to page 158 for instructions on the use of this ring.

This ring is to be used with T-480 portable Coll-O-Crimp and the T-420 collets ONLY.

T-480-AH



O-Crimp tooling, tooling packages and pumps

Refer to safety information regarding Coll-O-Crimp crimping procedures on page 159.

T-480-AH • Portable Coll-O-Crimp Press & Air/Hydraulic Pump Package

Capacity: 3/16" I.D. 1 fiber braid through 1-1/4" I.D. 6 spiral hose

Mounting: Free Standing Base

Size: 22-1/2" high, 14" long, 10-1/2" wide

Total Weight: 124 lbs.

Pump Specifications:

Dimensions: 5" high, 15-1/2" long, 5-5/8" wide

Pressure: 0-10,000 psi

Outlet Port Size: 3/8" NPT

Inlet Port: 1/4" NPT

Air Pressure: 60-100 psi

Hydraulic Oil: Enerpac

Reservoir Capacity: 36 cu. in.

Includes T-480-68 blue pusher extension ring. Refer to page 159 for instructions on the use of this ring.

Note: It is recommended that a filter, regulator, lubricator, and air pressure gauge be installed upstream from the pump. Filter, regulator and lubricator units are not included.

This ring is to be used with T-480 portable Coll-O-Crimp and the T-420 collets ONLY.