


Equipment

Coll-O-Crimp Portable T-480

 Refer to safety information regarding Coll-O-Crimp hose, hose fittings and assembly equipment compatibility on pages 3-4.

T-480-TA



Refer to pages 170 through 178 for Coll-O-Crimp tooling, tooling packages and pumps.

Refer to safety information regarding Coll-O-Crimp crimping procedures on page 160.

T-480-TA • Portable Coll-O-Crimp Press & Turbo Air/Hydraulic Pump Package

Capacity: 3/16" I.D. 1 fiber braid through 1-1/4" I.D. 6 spiral hose
Mounting: Free Standing Base
Size: 22-1/2" high, 14" long, 10-1/2" wide
Total Weight: 116 lbs.

Pump Specifications:
Dimensions: 8-1/4" high, 14" long, 6-1/4" wide
Pressure: 0-10,000 psi
Outlet Port Size: 3/8" NPT
Inlet Port: 1/4" NPT
Air Pressure: 40-150 psi
Hydraulic Oil: Enerpac
Reservoir Capacity: 150 cu. in.

Includes T-480-68 blue pusher extension ring. Refer to page 160 for instructions on the use of this ring.

Note: It is recommended that a filter, regulator, lubricator, and air pressure gauge be installed upstream from the pump. Filter, regulator and lubricator units are not included.

This ring is to be used with T-480 portable Coll-O-Crimp and the T-420 collets ONLY.

T-480-EP



Refer to pages 170 through 178 for Coll-O-Crimp tooling, tooling packages and pumps.

Refer to safety information regarding Coll-O-Crimp crimping procedures on page 161.

T-480-EP • Portable Coll-O-Crimp Press & 120v Electric Pump Package

Capacity: 3/16" I.D. 1 fiber braid through 1-1/4" I.D. 6 spiral hose
Mounting: Free Standing Base
Size: 22-1/2" high, 14" long, 10-1/2" wide
Total Weight: 134 lbs.

Pump Specifications:
Electrical Power Source: 15amp, 120v grounded 1Ph 50/60HZ
Dimensions: 14-1/4" high, 9-5/8" long, 9-5/8" wide
Pressure: 0-10,000 psi
Outlet Port Size: 3/8" NPT
Hydraulic Oil: Enerpac
Reservoir Capacity: 115.5 cu. in.
Flow: .5 to 1.0 gpm
Motor Rating: 1/2" hp universal, 9 amps at 10,000 psi

Includes T-480-68 blue pusher extension ring. Refer to page 161 for instructions on the use of this ring.

This ring is to be used with T-480 portable Coll-O-Crimp and the T-420 collets ONLY.