



# Equipment


## Coll-O-Crimp T-400

 Refer to safety information regarding Coll-O-Crimp hose, hose fittings and assembly equipment compatibility on pages 3-4.




**Note:** 25 ton (T-400-1 is C-O-C press only)

Refer to safety information regarding Coll-O-Crimp crimping procedures on page 164.



**Note:** Remove locator assembly when crimping bent tube ends.

 **CAUTION**  
 The Coll-O-Crimp power source has the pressure relief valve set at 4,000 to 4,200 PSI. Damage to the press will result if higher pressures are used and warranty may be voided.

### T-400 Coll-O-Crimp I Press/Pump Packages Continued

The T-400 Coll-O-Crimp I Press and tooling package can be supplied with a variety of power units for your particular needs. Listed below are press/power unit packages. For cabinets see pages 183-184.

### T-403 • C-O-C I & Hand Pump Package

Includes one each of the following:

CATALOG NUMBER	DESCRIPTION
T-400	Press and tooling package/Less T-400-16
T-403-2	Hand Pump
T-400-19	60" hose assembly and fittings

### T-414 • C-O-C I & 12v Electric Pump Package

Includes one each of the following:

CATALOG NUMBER	DESCRIPTION
T-400	Press and tooling package
T-412	12 volt DC Electric Pump

### T-400-9 • Crimp Locator

The T-400-9 allows you to make large volumes of hose assemblies by automatically aligning hose ends in proper crimp location.

#### Installation Procedure

1. Remove the front Allen bolt using an Allen wrench or tool provided with kit.

2. Add the washer provided with the kit to existing washer as shown and torque the bolt down to approximately 75 ft.-lbs.

3. Attach the locator post of the pre-assembled locator to the bottom of the middle plate and lock it in place with one of the knurled nuts.

4. Align the dimples on the first assembly with top of collet to locate the crimp. Drop the locator bracket down to rest on top of the hose end. Lock the bracket in position with remaining two knurled nuts. The locator now can be used, instead of dimples, to locate crimp accurately and consistently on the remaining hose ends of the same size and type.

### T-400-1 Coll-O-Crimp I Repair and Replacement Items

CATALOG NUMBER	DESCRIPTION
T-400-B	Pusher Bolt
T-400-BB	Switch to interface T400-1 crimper to T421U pump or T-421U-110 pump
W-EQCR-TD003-E	Shroud Decal
T-400-G	1.5 oz. Tube High Efficiency Teflon Grease
T-400-K1	Seal Replacement Kit for T-400-1 Press
T-400-M	Instructions for T-400-1
T-400-S	Replacement press shroud with Decals.
T-400-8	Die Ring
T-400-13	Replacement collet cage for T-400 'U' Series collets, 1/4" and 3/8" sizes only, and 229 "P" Series collets, all sizes, with a 'C' suffix (2 required for each collet).
T-400-14	Replacement collet cage for T-400 'U' Series collets with a 'C' suffix, 1/2" through 1" only, (2 required for each collet).
T-400-90	Replacement collet cage for T-400 'E', 069 'E', and 'E' Series collets with a 'C' suffix (2 required for each collet).
T-432-15	Pusher