

Equipment

Coll-O-Crimp Pumps

T-402-2 • Air/Hydraulic Pump



(Some models have air port on right side)

For use with T-400-1.

Pump Specifications:

Dimensions: 5-1/4" high, 12-1/2" long, 5" wide

Weight: 18 lbs.

Operation Pressure: 4,000-4,200 PSI

Reservoir Capacity: 1 pint

Hydraulic Oil: Use Enerpac Oil ONLY

Outlet Port Size: 3/8" NPT

Inlet (Air) Port Size: 1/4" NPT

Air Pressure: 60 to 120 PSI

Filter: F23A3T02

Regulator: R23RGL02

Lubricator: L43MPL00

Note: It is recommended that a filter, regulator, lubricator and air pressure gauge be installed in the air line as close as possible to the pump. Filter, Regulator and Lubricator units not included.

T-403-2 • Hand Pump



For use with T-400-1.

Pump Specifications:

Dimensions: 7 high, 21" long, 4-3/4" wide

Weight: 9 lbs.

Operation Pressure: 4,000-4,200 PSI


Reservoir Capacity: 1 qt.

Outlet Port Size: 3/8" NPT

Hydraulic Oil: Use Enerpac Oil ONLY

T-400-36 Bracket for mounting T-403-2 Hand Pump to FH-135X cabinet.

T-411 • Electric Pump (220v) Kit



Replacement pump for T-410-1 C-O-C II Plus Press ONLY.

Kit consists of:

T-421U Electric Pump (220v)

T-410-BB Pump switch for

T-410-1 crimping using

T-421U pump.

Replacement Parts:

CATALOG NUMBER	DESCRIPTION
T-411-B	By-pass module
T-411-G	Release Handle Spring (Models prior to 1982)
T-411-S	Micro-Switch (Models prior to 1982)
T-401-1B	Replacement Gasket between motor and square reservoir
T-421-FP	220v 4 wire Female electrical receptacle. See page 245 for illustration.
T-401-1BC	Breather Cap for Fenner-Stone pumps
T-401-1G	Relief Handle Spring (Models prior to 1982)
T-401-1S	Toggle Switch
T-401-SVF	Fenner Shuttle Valve

For repair and replacement items for the following pumps please contact an Enerpac Distributor at www.enerpac.com: T-402-2, T-403-2, T-460-2, T-462-2, T-480-2, T-480-3, T-481-110 & T-482-2.