

Equipment

Coll-O-Crimp Pumps

T-412 • Mobile Electric Pump



For use with T-400-1 and T-420-1.

Pump Specifications:

Dimensions: 7-1/2" high, 14-1/2" long, 9" wide

Weight: 65 lbs.

Operation Pressure: 4,000-4,200 PSI

Reservoir Capacity: 3 quarts

Outlet Port Size: 3/4"-16 straight thread

Motor: 12 volt D.C.

Hydraulic Oil: SAE 10W hydraulic oil or (ATF) automatic transmission fluid


Flow: 0.5 GPM

Replacement Parts:

T-401-1B Replacement Gasket between motor and square reservoir

T-401-1BC Breather Cap for Fenner-Stone pumps

T-421U • Electric Pump (220 Volt)



For use with T-400-1 and T-420-1.

Pump Specifications:

Dimensions: 7-1/2" high, 22" long, 10" wide

Weight: 75 lbs.

Operation Pressure: 4,000-4,200 PSI

Reservoir Capacity: 6 quarts

Outlet Port Size: 3/4"-16 Straight Thread

Motor: 1 H.P., 3450 R.P.M., 220 volts, 60 cycle, single phase

At 50 Hertz, RPM = 2,850

At 60 Hertz, RPM = 3,450

Hydraulic Oil*: ISO 32 hydraulic oil or (ATF) automatic transmission fluid

Flow: 2.5 GPM @ 750 PSI, 0.5 GPM @ 4000 PSI

Replacement Parts:


T-421-FP 220v 4 wire

Female electrical receptacle. See page 178 for illustration.

*For low temperature applications automatic transmission fluid can be substituted.

Note: It is recommended that the electric pump be used on a 15 amp. fused circuit. Pump wired for 220 volts, single phase.

T-421U-110 • Electric Pump (110 Volt)



For use with T-400-1 and T-420-1.

For dimensional data other than voltage information, refer to T-421U above.

Replacement Parts:

T-421U-BC Breather Cap

Note: It is recommended that the electric pump be used on an individual 30 amp. fused circuit.

Pump wired for 110 volts, single phase.