

Shank Type Fittings

PF Shank King Combination Nipples

- PF shank King Combination nipples have the same shank pattern as found on the PF style cam and groove fittings sold on page 36. This shank design was developed specifically for chemical transport hoses having Crosslinked Polyethylene (XLPE) or Ultra High Molecular Weight Polyethylene (UHMW) tubes, where shank retention can be a problem when using conventional band clamps.
- Recommended for discharge and suction service
- Not intended for compressed air

Plated Steel

Part #

ST25PF

ST35PF

ST40PF

ST60PF

ST80PF †

Size

2"

3"

4"

6"

PSI

250

125

100

75

45

- ALERT
- Working pressure is given at 70°F maximum

NPT end

150.00

The working pressure may vary with the construction of the hose, the type of clamping system used and the application. Consult the factory for recommendations.

SAFETY

eel		Stainless St	eel
Price/E	PSI	Part #	Price/E
		RST25PF	
		RST35PF	
47.30	100	RST40PF	170.00
109.20	75	RST60PF †	425.00



† Will be discontinued as inventory is depleted.

Note: Beveled ends for welding are also available. Contact the factory for further information.

Tuff-Lite King Combination Nipples

NPT end

Size	Polypropylene Part #	Price/E	Pkg Qty
1/2"	PPN44 *	\$.68	50
3/4"	PPN66 *	.75	50
1"	PPN88 *	1.10	25
1½"	HB150	4.40	25
2"	HB200	5.60	24
3"	HB300	13.50	10
4"	HB400	33.15	

NPT end

Size	Nylon Part #	Price/E	Pkg Qty
11/4"	THN15	\$5.35	25
1½"	THN20	5.80	25
2"	THN25	9.55	25
3"	THN35	20.10	10

* Sold in package quantities only.



PPN



HB



THN

DPL108 219



Call Toll Free: 1-866-71

We Ship World Wide

