## Adapters and Couplers with Straight Pipe Thread (NPSM)

For delivery of dry goods





Size	Aluminum <b>Part</b> #
4"	400-AS-AL



Boss-Lock

Size	Aluminum <b>Part #</b>	Stainless Steel Part #
4"	ADS400	RDS400



Dixon Coupler

Size	Aluminum Part #	Iron <b>Part</b> #
4"	400-DS-AL	400-DS-MI

Vegetable fiber gaskets are standard in threaded end. Replacement fiber gasket Part # 400GAGFI

## Railroad Tank Car Connections

Tank Car Connections are also available in other materials and in 2" and 2½" sizes. Consult factory for pricing and availability.



Style S \*\*

Swivel	Shank	Aluminum	Iron
Nut*		<b>Part</b> #	<b>Part #</b>
5"	3"	ATCS30	TCS30
5"	4"	ATCS40	TCS40



Style T \*\*

Swivel	Male	Aluminum	Iron
Nut*	NPT	<b>Part #</b>	<b>Part</b> #
5"	3"	ATCT30	TCT30
5"	4"	ATCT40	TCT40



Style T \*\*

Swivel Nut*	Male NPT	Stainless Steel  Part #
5"	3"	RTCT30
5"	4"	RTCT40



Style A \*\*

Swivel Nut*	Adapter	Stainless Steel Part #
5"	3"	RTCA30
5"	4"	RTCA40

**Note:** Stainless steel Railroad Tank Car Connections are not compatible with aluminum and brass

- \* All swivel nuts have standard Railroad Tank Car Thread.
- \*\* All sizes 20° below horizontal, except 3" threaded, which is 30° below horizontal.